



MIL-SPEC Series Field Wireable Plugs







3, 4 & 5 Conductor 5015 Industrial Equiv. Field Wireable Plugs, 16-18AWG



Field Wireable Plugs | Size 18 | 600 Volt, 13/10/8 amps MAX | IP67 Rating



F
MIL-SPEC

# of Poles	Male Faceview	Rating	Wire AWG	Cable O.D. Range	Male Plugs	Female Plugs
3	 18-3 1.1250-18UNEF	600V Max 13A Max	16-18 AWG	8-16 mm	MS18-3MP-FW25-SC	MS18-3FP-FW25-SC
	 18-4 1.1250-18UNEF	600V Max 10A Max	16-18 AWG	8-16 mm	MS18-4MP-FW25-SC	MS18-4FP-FW25-SC
5	 18-5A 1.1250-18UNEF	600V Max 8A Max	16-18 AWG	8-16 mm	MS18-5AMP-FW25-SC	MS18-5AFP-FW25-SC
	 18-5B 1.1250-18UNEF	600V Max 8A Max	16-18 AWG	8-16 mm	MS18-5BMP-FW25-SC	MS18-5BFP-FW25-SC
	 18-5C 1.1250-18UNEF	600V Max 8A Max	16-18 AWG	8-16 mm	MS18-5CMP-FW25-SC	MS18-5CFP-FW25-SC
	 18-5D 1.1250-18UNEF	600V Max 8A Max	16-18 AWG	8-16 mm	MS18-5DMP-FW25-SC	MS18-5DFP-FW25-SC

Voltage and Amperage ratings are cable dependent and are based on 600V 16AWG Cable.

Insert clocking, where available, is indicated by placing 'A, B, C or D' after the pin count in the part number. (e.g. MS18-5MP-** becomes MS18-5AMP-**)

Termination made by solder cup.