






MIL-SPEC Series Receptacles

2 & 3 Conductor 5015 Industrial Equiv. Receptacles



Panel Mount Receptacles | Size 14S | IP67 Rating

# of Poles	Male Faceview	Color Code	Rating	Wire AWG	Male Receptacles	Female Receptacles
2	 14S-2 0.8750"-20UNEF	North American A. White B. Black	600V 13A	16 AWG	MS14S-2MR-PM	MS14S-2FR-PM
			300V 10A	18 AWG	MS14S-2MR-18-PM	MS14S-2FR-18-PM
			300V 4A	22 AWG	MS14S-2MR-22-PM	MS14S-2FR-22-PM
3	 14S-3A 0.8750"-20UNEF	North American A. Green/Yellow B. Black C. White	600V 13A	16 AWG	MS14S-3AMR-PM	MS14S-3AFR-PM
			300V 10A	18 AWG	MS14S-3AMR-18-PM	MS14S-3AFR-18-PM
			300V 4A	22 AWG	MS14S-3AMR-22-PM	MS14S-3AFR-22-PM
	 14S-3B 0.8750"-20UNEF	North American A. Green/Yellow B. Black C. White	600V 13A	16 AWG	MS14S-3BMR-PM	MS14S-3BFR-PM
			300V 10A	18 AWG	MS14S-3BMR-18-PM	MS14S-3BFR-18-PM
			300V 4A	22 AWG	MS14S-3BMR-22-PM	MS14S-3BFR-22-PM
	 14S-3C 0.8750"-20UNEF	North American A. Green/Yellow B. Black C. White	600V 13A	16 AWG	MS14S-3CMR-PM	MS14S-3CFR-PM
			300V 10A	18 AWG	MS14S-3CMR-18-PM	MS14S-3CFR-18-PM
			300V 4A	22 AWG	MS14S-3CMR-22-PM	MS14S-3CFR-22-PM

0.3m leads are standard. Longer lead lengths are available, please consult the factory for part numbers.

Specifications:

Shell: Nickel Plated Zinc Diecast
Insulator: PBT
Contacts: Copper Alloy with Silver Plating
Gasket: NBR
Insert: PBT
Temperature: -40°C to +105°C (-40°F to +221°F)

