







MIL-SPEC Series Receptacles

3, 4 & 5 Conductor 5015 Industrial Equiv. Receptacles



Panel Mount Receptacles | Size 18 | Solder Cup | IP67 Rating

F
MIL-SPEC

# of Poles	Male Faceview	Rating	Wire AWG	Male Receptacles	Female Receptacles
3	 18-3 1.1250-18UNEF	600V Max 13A Max	16-18 AWG	MS18-3MR-PM-SC	MS18-3FR-PM-SC
4	 18-4 1.1250-18UNEF	600V Max 10A Max	16-18 AWG	MS18-4MR-PM-SC	MS18-4FR-PM-SC
5	 18-5A 1.1250-18UNEF	600V Max 8A Max	16-18 AWG	MS18-5AMR-PM-SC	MS18-5AFR-PM-SC
	 18-5B 1.1250-18UNEF	600V Max 8A Max	16-18 AWG	MS18-5BMR-PM-SC	MS18-5BFR-PM-SC

Voltage and Amperage ratings are cable dependent and are based on 600V 16AWG Cable.

Termination made by solder cup.

Specifications:

Shell: Nickel Plated Zinc Diecast
 Insulator: PBT
 Contacts: Copper Alloy with Silver Plating
 Gasket: NBR
 Insert: PBT
 Temperature: -40°C to +105°C (-40°F to +221°F)

