




MAC (1/2"-20) Series Field Wireable Plugs

3 Conductor MAC Series Field Wireable Plugs, 18-24AWG




Field Wireable Plugs | PG7 & PG9 Threads | 250 Volt, 4 amps | IP67 Rating



# of Poles	Male Faceview	Rating	Wire AWG	Cable O.D. Range	Male Receptacles		Female Receptacles	
					Straight	Right Angle	Straight	Right Angle
3	 1/2"-20	250V 4A	18-24 AWG	4-6 mm	MAC-3MP-FW07	MAC-3MP-FW07-R	MAC-3FP-FW07	MAC-3FP-FW07-R
				6-8 mm	MAC-3MP-FW09	MAC-3MP-FW09-R	MAC-3FP-FW09	MAC-3FP-FW09-R

These connectors have screw terminal connections.


Male Field Wireable Plugs



Straight Plugs

Right Angle Plugs

Female Field Wireable Plugs



Straight Plugs

Right Angle Plugs

Specifications:

Body:	Black Polyamide
Insulator:	Polyamide
Contacts:	Copper Alloy with Gold Plating
Coupling Nut:	Nickel Plated Brass
Seal:	NBR
Connections:	Screw Terminals
Temperature:	-40°C to +105°C (-40°F to +221°F)

G

Micro-AC Series (1/2"-20) Cordsets