







MAC (1/2"-20) Series Receptacles

2, 3, 4, 5 & 6 Conductor MAC Series Receptacles, 18/22AWG




Male Front Mount Receptacles | PG9 & PG13.5 Threads | 300 Volt, 4 amps | IP69 Rating




# of Poles	Male Faceview	Color Code	Rating	Wire AWG	Male Receptacles	
					PG9	PG 13.5
2	 1/2"-20	1. Brown 2. Blue	300V 4A	18 AWG	MAC-2MR-PG9-18	MAC-2MR-PG13.5-18
				22 AWG	MAC-2MR-PG9	MAC-2MR-PG13.5
3	 1/2"-20	1. Green/Yellow 2. Red/Black 3. Red/White	300V 4A	18 AWG	MAC-3MR-PG9-18	MAC-3MR-PG13.5-18
				22 AWG	MAC-3MR-PG9	MAC-3MR-PG13.5
4	 1/2"-20	1. Red/Black 2. Red/White 3. Red 4. Green/Yellow	300V 4A	18 AWG	MAC-4MR-PG9-18	MAC-4MR-PG13.5-18
				22 AWG	MAC-4MR-PG9	MAC-4MR-PG13.5
5	 1/2"-20	1. Red/White 2. Red 3. Green/Yellow 4. Red/Yellow 5. Red/Black	300V 4A	18 AWG	MAC-5MR-PG9-18	MAC-5MR-PG13.5-18
				22 AWG	MAC-5MR-PG9	MAC-5MR-PG13.5
6	 1/2"-20	1. Red/White 2. Red 3. Green/Yellow 4. Red/Yellow 5. Red/Black 6. Red/Blue	300V 4A	22 AWG	MAC-6MR-PG9	MAC-6MR-PG13.5

12" leads are standard. Longer lead lengths are available, please consult the factory for part numbers.

PG9 Threads



PG13.5 Threads



Specifications:

Shell: PG 9: Nickel Plated Brass
PG 13.5: Clear Anodized Aluminum
Insulator: Polyamide
Wire: 18 & 22 AWG: UL Style 1007/1569, 300V

Contacts: Copper Alloy with Gold Plating
O-Ring: NBR
Jam Nut: Nickel Plated Brass
Temperature: -40°C to 105°C (-40°F to +221°F)