





# MDC (M12) Series Cordsets

5 Conductor MDC Series Cordsets, 18/22AWG



Double Ended Cordsets | Straight | 300 Volt, 4 amps | IP69 Rating




Male Faceview	Part Number	Cables	Features	Color Code	Female Faceview
 M12 x 1	MDC-5MFPX-**	Yellow PVC AWM <b>5 X 18 AWG</b> 300V, 4A -40°C to +80°C 7.4mm OD	Industry Standard PVC	1. Brown 2. White 3. Blue 4. Black 5. Gray	 M12 x 1
	MDC-5MFP-**	Yellow PVC AWM <b>5 X 22 AWG</b> 300V, 4A -40°C to +105°C 5.8mm OD	Industry Standard PVC		
	MDCM-5MFP-**	Yellow PVC AWM With Foil Shield <b>5 X 22 AWG</b> 300V, 4A -40°C to +105°C 5.8mm OD	Industry Standard PVC Foil Shield		
	MDCM-5MFPS-**	Yellow PVC AWM With Foil Shield <b>5 X 22 AWG</b> 300V, 4A -40°C to +105°C 5.8mm OD	Industry Standard PVC Foil Shield to the Coupling Nut		
	MDCP-5MFP-**	Yellow PUR AWM <b>5 X 22 AWG</b> 300V, 4A -40°C to +80°C 5.8mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		
	MDCWF-5MFP-**-B	Black TPE AWM <b>5 X 22 AWG</b> 300V, 4A -40°C to +105°C 5.2mm OD	Hi-Flex Weld Slag Resistant TPE		

\*\* Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Black and gray cables are available on some versions, please consult the factory.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "SS" suffix. (e.g. MDC-5MFP-1M becomes MDC-5MFP-1M-SS)



Male - Female Extension