



Ethernet Series Etherlink V3

8 Conductor Ethernet Series V3 Cordsets & Field Wireable Plugs, 24AWG



Field Wireable Plugs | Single & Double Ended Male Cordsets | UL Type 4, 6P | IP65 Rating

Patented by Mencom Corporation

It is recommended that quality Mencom cables are used with the field wireable connectors to assure an accurate fit. However, if using another brand, the dimensions of the connector must meet the dimensions shown below.




| Field Wireable Plugs | Part Number | Housing Specifications | Front View |
|----------------------|--------------|---|------------|
| | E45V3-8MP-FW | Coupling Nut : Body : O-Ring : Grommets : Tightening Torque: Max. Panel Thickness: Temperature : Black Anodized Aluminum Black Polyamide NBR NBR & TPE 4.0 N-m 5.5 mm -20°C to +80°C | |

Assembly Instructions




STEP 1)

Remove clip by cutting or by bending it back and forth until it breaks.



STEP 2)

With connector unassembled, push cable through dome nut, split apart the grommet and wrap it around the cable, then push the cable through the connector body.



STEP 3)

Push grommet back into the "fingers" of the shell. Rotate cable 90 degrees and pull it back into the connector until it stops. With slight tension on cable, tighten dome nut (3.75Nm recommended).

| E45V3 to Cable | | | | |
|-------------------------------------|------------|-------------------|--------------------|---------------|
| # of Poles | Front View | Part Number | | Housing Style |
| | | PVC Male | PUR Male | |
| 8 | | E45V3-8MP-** | E45V3P-8MP-** | |
| E45V3 to RJ45 | | | | |
| 8 | | E45V3-8MP-RJ45-** | E45V3P-8MP-RJ45-** | |
| E45V3 Male to Male Extension Cables | | | | |
| 8 | | E45V3-8MMP-** | E45V3P-8MMP-** | |

** Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.