



# 7/8" JIN Junction Blocks

6 Port, 3 Pin JIN Junction blocks



Standard Wiring | MIN Receptacle & Cable | IP67 Protection Rating

Trunk Style	Trunk Connection	Part Number	Circuit
	MIN Size II 8 Pole Male Receptacle	JIN-630-008-M000	
	Yellow PVC AWM 2661 <b>8 x 18 AWG</b> 300V 9mm OD	JIN-630-008-C**	

Cables for JIN-630-008-M000				Female Receptacle	
Single Ended Home Run Cable		Double Ended Home Run Cable			
MIN-8FPX-*	Page B-5	MIN-8MFPX-*	Page B-11	MIN-8FR2-1-18	Page B-17

\* Length in feet. Standard Cable lengths are 3, 6, 12, 20, 30 & 50 feet. Consult factory for other lengths.

\*\* Lengths in meters. Standard Cable lengths are 2, 5 & 10 meters. Consult factory for other lengths.

Standard housing is aluminum alloy, for stainless steel housing add a "SS" right after JIN. (e.g. JIN-630-008-M000 becomes JINSS-630-008-M000)

## Specifications:

Housing:	Black Epoxy Coated Die Cast Aluminum Alloy
Connectors:	Anodized Aluminum, Oil Resistant PVC Contact Carrier
Cable Gland:	Nickel Plated Brass, Polyamide and TPE Inserts
Contacts:	Copper Alloy with Gold Plating
Temperature:	-30°C to +80°C (-22°F to +176°F)
Amperage:	4A per Port, 8A per Unit