



Cable Glands

Metric Threads Cable Glands




Dual Grommet Plastic Cable Glands | Metric Threads | IP68 Rating



Part Number		UL Rating	Diameter Range (mm)	A Mounting Hole Clearance (mm)	B Thread Length (mm)	C Wrench Flats (mm)	Thread Type
Gray	Black						
PCGU-M12	PCGU-M12-B	UL Recognized	2 - 5	12.2	8	15	M12 X 1.5
PCGU-M16	PCGU-M16-B	UL Recognized	3 - 10	16.2	8	20	M16 X 1.5
PCGU-M20	PCGU-M20-B	UL Recognized	5 - 13	20.2	8	24	M20 X 1.5
PCGU-M25	PCGU-M25-B	UL Recognized	8 - 17	25.2	8	29	M25 X 1.5
PCGU-M32	PCGU-M32-B	UL Recognized	12 - 21	32.2	10	36	M32 X 1.5
PCGU-M40	PCGU-M40-B	UL Recognized	16 - 28	40.2	10	46	M40 X 1.5
PCGU-M50	PCGU-M50-B	UL Recognized	21 - 35	50.2	12	55	M50 X 1.5
PCGU-M63	PCGU-M63-B	N/A	27 - 48	63.2	12	68	M63 X 1.5

These Cable Glands have a dual grommet system that allows for a much wider range in diameter than the standard plastic cable glands. Cables that are in the lower part of the diameter range will fit into the cable gland without any change. For cables that are in the upper part of the diameter range, the dome nut is removed and the seals are removed. Separate the inner seal from the outer seal into the cable gland and then put the outer seal back in place. It is now ready for use with the larger cable.

A Locking Nut is supplied on all Metric threaded parts. An O-Ring is not needed on any sizes smaller than M32. An O-Ring is supplied on size M32 and larger.



Materials:

Body: Polyamide

Seal: Neoprene