



| Technical data | |
|--|--|
| Operating temperature range (min, max) | (-40°C ... +125°C) |
| Material | metal |
| IP degree of protection | IP66/ IP67 (EN 60529) and IP69K (DIN 40050 - 9) degree of protection |
| Weight | 510,00 g |
| Cable entry | 1" NPT |

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

| Description: | | | | | |
|--|------------|------------|---|------------|--------------|
| surface mounting housings with 2 stainless steel levers, high construction, size "104.27", 1" NPT, metal version, IP66 / IP67 | | | | | |
| UNLESS OTHERWISE SPECIFIED: | DRAWN BY | DCG | MENCOM CORPORATION | | |
| DIMENSIONS ARE IN MM TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 3° BEND ± 5° ONE PLACE DECIMAL ± .2 TWO PLACE DECIMAL ± .1 | DRAWN DATE | 04/01/2019 | | | |
| | CHECKED BY | JJH | | | |
| | CHECK DATE | 04/01/2019 | | | |
| | | | | | |
| | | | TITLE: 24 PL IP 67 V-TYPE SRFC MT BS | | |
| | | | | | |
| COMMENTS: | | | | | |
| MATERIAL | | | | | |
| FINISH | | | | | |
| DO NOT SCALE DRAWING | | | SIZE | DWG. NO. | REV |
| | | | B | C7APT-24.6 | A |
| | | | SCALE: 2:3 | WEIGHT: | SHEET 1 OF 1 |