


$$\begin{bmatrix} 77.5 \\ 3.1 \end{bmatrix}$$

[27]
1.1

SCREW INSERTS WITHOUT PLATE FOR SECTION CONDUCTORS

MATERIALS	
HOUSING:	GLASS REINFORCED THERMOPLASTIC
	NICKEL PLATED BRASS HARDWARE
SCREWS:	NICKEL PLATED BRASS
CONTACTS:	SILVER PLATED COPPER ALLOY
RATINGS:	UL - 600V, 35A. EN 400/690V/6kV/3, 35A
APPROVALS:	UL, CSA, & CCC

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.



UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

DRAWN BY

DRAWN DATE

CHECKED BY

CHECK DATE

COMMENTS:

DCG

03/14/2023

JJH

03/14/2023

MENCOM CORPORATION

TITLE:

6 PL MALE SCREW INSERT 35AMP W/O WP

SIZE

DWG. NO.

REV

SCALE: 1:1

WEIGHT:

SHEET 1 OF 1

B

CPM-06X

A