



PANEL CUTOUT

MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 6 JACK	CAT 6 JACK
ALL D-SUBS	FEMALE	MALE

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS					
BODY:	EPOXY COATED DIE CAST ALUMINUM	NEMA/UL EN 60529:		4, 4X, 12 IP65			
GASKET:	THERMOPLASTIC ELASTOMER	MOUNTING SCREW SIZE:		M4 (8-32) (304 or 316SS for 4X)			
HANDLE:	POLYAMIDE	MOUNTING SCREW TORQUE:		1.2~1.8N-m (0.9~1.3 Lb-Ft)			
LEVERS:	STAINLESS STEEL						
us	UNLESS OTHERWISE SPECIFIED:	DRAWN BY	DG	MENCORPORATION			
	DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	04/11/2019				
		CHECKED BY	DCG				
		CHECK DATE	04/11/2019				
				TITLE: DB9; RJ45; USB-BA; 24			
MATERIAL	COMMENTS:		SIZE			DWG. NO.	REV
FINISH			B			DB09-RJ45-USB-BFAF-24	C
DO NOT SCALE DRAWING			SCALE: 1:1			WEIGHT:	SHEET 1 OF 1



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCORPORATION IS PROHIBITED.