



(2X)USB 3.0 TYPE A CONFIGURED
FEMALE EXTERIOR / FEMALE INTERIOR

A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere rating of the protection provided.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

| HOUSING MATERIALS | |
|-------------------|--------------------------------|
| BODY: | EPOXY COATED DIE CAST ALUMINUM |
| GASKET: | THERMOPLASTIC ELASTOMER |
| HANDLE: | POLYAMIDE |
| LEVERS: | STAINLESS STEEL |

| PIC RATINGS/SPECIFICATIONS | |
|----------------------------|---------------------------------|
| VOLTS: | 125V |
| AMPS: | 15A |
| SCCR: | 10kA |
| NEMA/UL EN 60529: | 4, 4X, 12 IP65 |
| MOUNTING SCREW SIZE: | M4 (8-32) (304 or 316SS for 4X) |
| MOUNTING SCREW TORQUE: | 1.2~1.8N-m (0.9~1.3 Lb-Ft) |
| INCOMING POWER WIRE SIZE: | 0.5 ~ 4.0 sq mm / 20-12AWG |
| WIRE STRIP LENGTH: | 10 ~ 11 mm |

OPERATING TEMPERATURE: (-30°C / +66° C (-22° F / +150° F))

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M4x0.7 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

| | |
|-----------------------------------|--|
| UNLESS OTHERWISE SPECIFIED: | |
| DIMENSIONS ARE IN INCHES AND [MM] | |
| MATERIAL | |
| FINISH | |
| DO NOT SCALE DRAWING | |

| | |
|------------|------------|
| DRAWN BY | DCG |
| DRAWN DATE | 07/12/2021 |
| CHECKED BY | DCG |
| CHECK DATE | 07/15/2021 |

COMMENTS:

| MENCOM CORPORATION | | | |
|--------------------------------|--------------------------------|-----------------|--|
| TITLE: GF; 2 USB-AA; 32 | | | |
| SIZE B | DWG. NO. GF-2USB-AFAF-NR-32 | REV D | |
| SCALE: 2:3 | WEIGHT: | SHEET 1 OF 1 | |