



| STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED |             |             |
|--|-------------|-------------|
| CONN. TYPE                                     | EXTERIOR    | INTERIOR    |
| RJ45   | CAT. 6 JACK | CAT. 6 JACK |

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.



| HOUSING MATERIALS |                                |
|-------------------|--------------------------------|
| BODY:             | EPOXY COATED DIE CAST ALUMINUM |
| GASKET:           | THERMOPLASTIC ELASTOMER        |
| HANDLE:           | POLYAMIDE                      |
| LEVERS:           | STAINLESS STEEL                |

|                                   |  |
|-----------------------------------|--|
| UNLESS OTHERWISE SPECIFIED:       |  |
| DIMENSIONS ARE IN INCHES AND [MM] |  |
| MATERIAL                          |  |
| FINISH                            |  |
| DO NOT SCALE DRAWING              |  |

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

| PIC RATINGS/SPECIFICATIONS         |                                 |
|------------------------------------|---------------------------------|
| VOLTS:                             | 125V                            |
| AMPS:                              | 3A                              |
| SCCR:                              | 0.2kA                           |
| NEMA/UL   EN 60529:                | 4, 4X, 12   IP65                |
| MOUNTING SCREW SIZE:               | M4 (8-32) (304 or 316SS for 4X) |
| MOUNTING SCREW TORQUE:             | 1.2~1.8N-m (0.9~1.3 Lb-Ft)      |
| INCOMING POWER WIRE SIZE:          | 0.5 ~ 4.0 sq mm / 20-12AWG      |
| WIRE STRIP LENGTH:                 | 10 ~ 11 mm                      |
| MENCOM CORPORATION                 |                                 |
| TITLE:<br>GF; DB9 FF; RJ45; 3A; 32 |                                 |
| SIZE<br>B                          | DWG. NO.<br>GF-DB9F-RJ45-R-32   |
| SCALE: 2:3                         | WEIGHT:                         |
| SHEET 1 OF 1                       |                                 |