



WIRING CHART	WIRING CHART	
INCOMING POWER	RESET	GFDP1 (LINE) TERMINAL BLOCK
FACTORY WIRE	(X)	HOT (X)
BLACK (H)/CRIMP CONNECTOR	(X)	
WHITE (N)		NEUTRAL
GREEN (GND)		GROUND




5-15R GFCI SELF-TEST RCPT




5-15R SIMPLEX RCPT.
IN BACK

3 POLE TERMINAL BLOCK
FOR INCOMING POWER



PANEL CUTOUT



STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 6 JACK	CAT 6 JACK

OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140° F))

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M4x0.7 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

HOUSING MATERIALS	
BODY:	EPOXY COATED DIE CAST ALUMINUM
GASKET:	THERMOPLASTIC ELASTOMER
HANDLE:	POLYAMIDE
LEVERS:	STAINLESS STEEL



UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS

VOLTS:	125V
AMPS:	10A
SCCR:	0.2kA
NEMA/UL EN 60529:	4, 4X, 12 IP65
MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)
MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)
INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
WIRE STRIP LENGTH:	7 ~ 8 mm

MENCOM CORPORATION

TITLE:
GFI SEMPLX BM; RJ45; 10A; 32

SIZE	DWG. NO.	REV
B	GFDP1-RJ45-10R-32	C
SCALE: 2:3	WEIGHT:	SHEET 1 OF 1