PANEL CUTOUT

[117.0 +0.4 0.0]
4.61 +0.02 -0.00

[91.0 +0.4 0.0]
3.58 +0.02 -0.00

[2.0 MAX]
R0.08 MAX



[130.2]
5.13

RJ45 Cat 6 Jack
INTERIOR/EXTERIOR

USB TYPE B FEMALE (EXTERIOR)
TO TYPE B FEMALE (INTERIOR)



[123.6]
4.87

[79.7]
3.14

[116.9]
4.60

3 POLE PLUGGABLE
TERMINAL BLOCK
FOR INCOMING POWER



[25.1]
0.99

(X4) USE PH2 SCREW DRIVER ON MOUNTING SCREWS. (REF. MOUNTING SCREW TORQUE)

ROTATE TWO TURNS COUNTER CLOCKWISE TO RELEASE THE TURN BUCKLE PRIOR TO TIGHTENING

TURN BUCKLES ROTATE 90 DEG. INTO THEIR CLAMPING POSITION AS MOUNTING SCREWS TIGHTEN. DO NOT OVER-TORQUE!



SLIDE LATCH TO OPEN/CLOSE
ROTATE LOCK TO LOCK CLOSED

LOCK



DETAIL A
SCALE 1 : 1

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS	
VOLTS:	125V
AMPS:	3A
SCCR:	0.2kA
NEMA/UL | EN 60529:	4, 12 | IP65
PANEL THICKNESS:	5.0mm max
MOUNTING SCREW TORQUE:	0.8N-m
TERMINAL BLOCK TORQUE:	0.5N-m
INCOMING POWER WIRE SIZE:	0.25 - 2.5 sq mm / 24-12AWG
WIRE STRIP LENGTH:	7 - 8 mm

c UL us
LISTED
ENCL. ACC.
5JR2

HOUSING MATERIALS	
BODY:	NICKEL PLATED ZINC
GASKETS:	PUR FIPG
FRONT COVER:	POLYCARBONATE
LATCH & LOCK:	PBT
BACK COVER:	POLYPROPYLENE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES AND [MM]
MATERIAL
FINISH
DO NOT SCALE DRAWING

DRAWN BY	DG
DRAWN DATE	04/01/2019
CHECKED BY	DCG
CHECK DATE	04/01/2019

COMMENTS:

MENCOM CORPORATION

TITLE:
DPLX; RJ45; USB-BA; 3A; LP3

SIZE	DWG. NO.	REV
B	LP3-DP-RJ45-USB-BFAF-R	B

SCALE: 1:2 | WEIGHT: | SHEET 1 OF 1