

WIRING
1--1
2--2
3--3
4--4

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	DRAWN IN SW	5/21/2013	DCT

TABLE A	
P/N	L
MDC-4MFP-0.3M-A03	12"[0.3M]
MDC-4MFP-0.5M-A03	19"[0.5M]
MDC-4MFP-1M-A03	40"[1M]
MDC-4MFP-1.5M-A03	59"[1.5M]
MDC-4MFP-2M-A03	79"[2M]
MDC-4MFP-3M-A03	118"[3M]
MDC-4MFP-4M-A03	157"[4M]
MDC-4MFP-5M-A03	197"[5M]
MDC-4MFP-6M-A03	236"[6M]
MDC-4MFP-7M-A03	276"[7M]
MDC-4MFP-8M-A03	315"[8M]
MDC-4MFP-9M-A03	355"[9M]
MDC-4MFP-10M-A03	393"[10M]
MDC-4MFP-12M-A03	473"[12M]
MDC-4MFP-14M-A03	551"[14M]
MDC-4MFP-15M-A03	590"[15M]
MDC-4MFP-20M-A03	786"[20M]
MDC-4MFP-25M-A03	983"[25M]
MDC-4MFP-30M-A03	1179"[30M]



MATERIALS	
BODY:	BLACK PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE:	22/4 AWM 2661 YELLOW JACKET
COUPLING:	NICKEL PLATED BRASS
INSERT:	POLYAMIDE
O-RING:	VITON
ARMOR:	SS FLEX TUBE, BLK PVC JACKET

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

VOLTS	300V
AMPS	4A
UL?:	YES
SPECIFICATIONS	

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL $\pm 1/64$
ANGULAR: MACH $\pm 5^\circ$ BEND $\pm 5^\circ$
ZERO PLACE DECIMAL $\pm .5$
ONE PLACE DECIMAL $\pm .1$
TWO PLACE DECIMAL $\pm .01$
THREE PLACE DECIMAL $\pm .004$

	NAME
DRAWN	JJH
CHECKED	
ENG APPR.	
MFG APPR.	
Q.A.	
COMMENTS:	

MENCOM CORPORATION

TITLE:

SIZE B	DWG. NO. MDC-4MFP-ZZ-A03	REV B
SCALE: 1:1	WEIGHT:	SHEET 1 OF