


PIN #	COLOR
1	BROWN
2	WHITE
3	BLUE
4	BLACK

D

C

B

A



MATERIALS	
BODY:	BLACK PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE:	
STYLE:	AWM
AWG:	22 AWG
JACKET:	YELLOW PVC
VOLTAGE:	600V
SHIELD:	NO
COUPLING:	STAINLESS STEEL
INSERT:	POLYAMIDE
ARMOR:	SS FLEX TUBE, BLACK PVC JKT
HEAT SHRINK:	POLYOLEFIN
APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED
ROHS:	YES
CE:	YES
RATINGS	
PROTECTION CLASS:	UL TYPE 4 & 12, IEC IP69

NOTE: ARMOR CANNOT BE CUT BY USER WITHOUT DAMAGING UNDERLYING CABLE.
12" [0.3M] OF FREE CABLE PROTRUDE FROM END OF ARMOR.

FOR CUSTOM LENGTHS OR EXTRA CABLE PROTRUDING FROM END OF ARMOR, PLEASE CONSULT FACTORY.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS	300V
AMPS	4A
TEMP:	105°C

UNLESS OTHERWISE SPECIFIED:	DRAWN BY	JJH
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	08/17/2021
	CHECKED BY	ADM
	CHECK DATE	08/17/2021
	COMMENTS:	
MATERIAL		
FINISH		
DO NOT SCALE DRAWING		

TABLE A		
P/N	L	STD?
MDC-4MP-1M-A03-SS	40" [1M]	YES
MDC-4MP-2M-A03-SS	79" [2M]	YES
MDC-4MP-3M-A03-SS	118" [3M]	NO
MDC-4MP-4M-A03-SS	157" [4M]	NO
MDC-4MP-5M-A03-SS	197" [5M]	YES
MDC-4MP-6M-A03-SS	236" [6M]	NO
MDC-4MP-7M-A03-SS	276" [7M]	NO
MDC-4MP-8M-A03-SS	315" [8M]	NO
MDC-4MP-9M-A03-SS	355" [9M]	NO
MDC-4MP-10M-A03-SS	393" [10M]	YES

PARTS LISTED AS NOT BEING STANDARD MAY HAVE MINIMUM ORDER QUANTITIES

MENCOM CORPORATION		
TITLE:		
SIZE	DWG. NO.	REV
B	MDC-4MP-ZZ-A03-SS	A
SCALE: 1:1	WEIGHT:	SHEET 1 OF 1