



PIN # COLOR

- 1 BLACK
- 2 WHITE
- 3 RED
- 4 GREEN / YELLOW

7/8-16UN2A

M20x1.5

25.4  
1.0

17.0  
.67

6.1  
.24

TABLE A

P/N	L
MIN-4FR-0.5-M20	6" [0.15M]
MIN-4FR-1-M20	12" [0.3M]
MIN-4FR-2-M20	24" [0.6M]
MIN-4FR-3-M20	36" [0.91M]
MIN-4FR-4-M20	48" [1.2M]
MIN-4FR-5-M20	60" [1.5M]
MIN-4FR-6-M20	72" [1.8M]
MIN-4FR-10-M20	120" [3M]

OTHER LENGTHS AVAILABLE  
PLEASE CONSULT FACTORY

MENCOM CORPORATION

TITLE:		
SIZE	DWG. NO.	REV
B	MIN-4FR-ZZ-M20	B
SCALE: 2:1	WEIGHT:	SHEET 1 OF 1

MATERIALS	
SHELL:	CLEAR ANODIZED ALUMINUM
CONTACTS:	GOLD PLATED COPPER ALLOY
WIRES:	
STYLE:	UL 1015
AWG:	16/4
JACKET:	PVC
VOLTAGE:	600V
INSERT:	YELLOW PVC
O-RING:	NBR
NUT:	NICKEL PLATED BRASS
APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED
ROHS:	YES
CE:	YES
RATINGS	
PROTECTION CLASS:	UL TYPE 4 & 12, IEC IP69

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.

VOLTS 600V  
AMPS 10A  
TEMP: 105°C

UNLESS OTHERWISE SPECIFIED:		DRAWN BY	ADM
DIMENSIONS ARE IN INCHES AND [MM]		DRAWN DATE	03/08/2022
		CHECKED BY	JJH
		CHECK DATE	03/08/2022
		COMMENTS:	
MATERIAL			
FINISH			
DO NOT SCALE DRAWING			