	WIRING	
1	———	1
2	———	2
3	———	3







DETAIL A
SCALE 4 : 1



DETAIL B
SCALE 4 : 1

TABLE A		
P/N	L	STD?
NAN-T-3MFP-0.5M-R	19"[.5M]	NO
NAN-T-3MFP-1M-R	40"[1M]	YES
NAN-T-3MFP-2M-R	79"[2M]	YES
NAN-T-3MFP-3M-R	118"[3M]	NO
NAN-T-3MFP-4M-R	157"[4M]	NO
NAN-T-3MFP-5M-R	197"[5M]	YES
NAN-T-3MFP-6M-R	236"[6M]	NO
NAN-T-3MFP-8M-R	315"[8M]	NO
NAN-T-3MFP-10M-R	393"[10M]	YES
NAN-T-3MFP-15M-R	590"[15M]	YES
NAN-T-3MFP-20M-R	786"[20M]	NO

PARTS LISTED AS NOT BEING STANDARD
MAY HAVE MINIMUM ORDER QUANTITIES

MATERIALS:	
BODY:	BLACK POLYAMIDE/PVC BLEND
INSERT:	POLYAMIDE
CONTACTS:	GOLD PLATED COPPER ALLOY
COUPLING:	NICKEL PLATED BRASS
CABLE:	24/3 BLACK PVC

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS	60V
AMPS	3A
TEMP:	105°C

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

DRAWN BY	JJH
DRAWN DATE	03/29/2018
CHECKED BY	DWM
CHECK DATE	04/02/2018

COMMENTS:

MENCOM CORPORATION

TITLE:

SIZE	DWG. NO.	REV
B	NAN-T-3MFP-ZZ-R	A

SCALE: 2:1 | WEIGHT: | SHEET 1 OF 1