



2M20PA LOCK NUT INCLUDED BUT NOT SHOWN

NO O-RING IS NECESSARY TO OBTAIN IP68 SEAL. CRUSH RIBS ON THE UNDERSIDE OF HEX WILL PROVIDE THE SEAL.

MATERIALS	
BODY:	GRAY POLYAMIDE
GROMMET:	NEOPRENE

SPECIFICATIONS:	
TIGHTENING TORQUE:	3.75 Nm
TEMPERATURE:	-20°C - +100°C

APPROVALS:	
US	UL RECOGNIZED
CANADA	C-UL RECOGNIZED

PART NUMBER	COLOR	SEALING RANGE
PCG-M20RL	GRAY	5-9mm
PCG-M20RL-B	BLACK	5-9mm

UNLESS OTHERWISE SPECIFIED:		DRAWN BY	DCG	MENCOM CORPORATION		
DIMENSIONS ARE IN INCHES AND [MM]		DRAWN DATE	04/11/2017			
		CHECKED BY	ADM			
		CHECK DATE	04/12/2017			
				TITLE: PLSTC CBL GLND M20 THD 5-9MM		
MATERIAL		COMMENTS:		SIZE	DWG. NO.	REV
FINISH				B	PCG-M20RL	A
DO NOT SCALE DRAWING				SCALE: 3:1	WEIGHT:	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCON CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCON CORPORATION IS PROHIBITED.