



REVISIONS		
REV.	DESCRIPTION	DATE
A	REDRAWN IN SW	5/8/2007

NO O-RING IS NECESSARY TO OBTAIN IP68 SEAL.  
CRUSH RIBS ON THE UNDERSIDE OF HEX WILL  
PROVIDE THE SEAL.

SEAL RATED TO: IP68

LOCK NUT INCLUDED BUT NOT SHOWN

MATERIALS	
BODY:	GRAY OR BLACK POLYAMIDE
GROMMET:	CR/NBR - OUTER PART TPE / INNER PART

SPECIFICATIONS:	
TIGHTENING TORQUE:	2.7 Nm
TEMPERATURE:	-20°C - +100°C

APPROVALS:	
US	UL RECOGNIZED
CANADA	C-UL RECOGNIZED

PART NUMBER	COLOR	SEALING RANGE
PCGU-M20L	GRAY	5-13mm
PCGU-M20L-B	BLACK	5-13mm

UNLESS OTHERWISE SPECIFIED:		NAME	
DIMENSIONS ARE IN INCHES		DRAWN	ADM
		CHECKED	
		ENG APPR.	
		MFG APPR.	
		Q.A.	
		COMMENTS:	
MATERIAL		MENCOM CORPORATION	
FINISH		TITLE:	
		PLASTIC CABLE GLAND M20	
		SIZE	REV
		B	A
		DWG. NO.	
		PCGU-M20L	
		SCALE: 2:1	SHEET 1 OF 1
		WEIGHT:	

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.

SPECIFICATIONS	DO NOT SCALE DRAWING