



Data sheet | Item number: 2000-5311

3-conductor sensor terminal block; for PNP (positive) switching sensors;
with colored conductor entries; 1 mm²; Push-in CAGE CLAMP®




2000-5311



RoHS
Compliant

[BOMcheck.net](https://www.bomcheck.net)

Color:



Item description

3.5 mm spacing per signal (2 x 3.5 mm = 7 mm)

The double spacing per pole of this terminal block series maximizes connectivity. For example, ten sensors may be connected using only five sensor terminal blocks plus a power supply terminal block.

Data

Electrical data

Ratings per IEC/EN 60664-1

Rated voltage (III / 3)	250 V
Rated impulse voltage (III / 3)	4 kV
Rated current	13.5 A

Approvals per CSA

Rated voltage CSA (Use Group C)	300 V
Rated current CSA (Use Group C)	10 A

Connection data

Connection technology	Push-in CAGE CLAMP®
Actuation type	Push-in Open Tool Slot
Connectable conductor materials	Copper
Nominal cross section	1 mm²
Solid conductor	0.14 ... 1.5 mm² / 24 ... 16 AWG
Solid conductor, push-in termination	0.5 ... 1.5 mm² / 20 ... 16 AWG
Fine-stranded conductor	0.14 ... 1.5 mm² / 24 ... 16 AWG
Strip length	9 ... 11 mm / 0.35 ... 0.43 inch
Note (conductor cross-section)	Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.
Total number of connection points	8
Total number of potentials	4
Type of wiring	Front-entry wiring

Geometrical Data

Width	7 mm / 0.276 inch
Height from upper-edge of DIN-35 rail	52.4 mm / 2.063 inch
Depth	81.1 mm / 3.193 inch

Mechanical data

Design	horizontal
Type of mounting	DIN-35 rail
Marking level	Center/side marking

Material Data

Color	gray
Insulating material	Polyamide 66 (PA 66)
Fire load	0 MJ
Weight	14.7 g

Commercial data

Country of origin	DE
GTIN	4055143393447
Customs Tariff No.	85369010000

Approvals / Certificates

Country specific Approvals

Logo	Approval	Additional Approval Text	Certificate name
	CSA DEKRA Certification B.V.	C22.2 No. 158	2130762

UL-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL UL International Germany GmbH	UL 1059	E45172 sec.55

Compatible products

Carrier rail

	Item no.: 210-112 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm	210-112
	Item no.: 210-113 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715	210-113

	Item no.: 210-114 Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715	210-114
	Item no.: 210-115 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm	210-115
	Item no.: 210-118 Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715	210-118
	Item no.: 210-196 Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715	210-196
	Item no.: 210-197 Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715	210-197
	Item no.: 210-198 Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715	210-198
Marking accessories		
	Item no.: 2009-110 Marking strips; on reel; not stretchable; plain; snap-on type	2009-110
	Item no.: 2009-113 WMB-Inline; for Smart Printer; on reel; plain; snap-on type	2009-113
	Item no.: 2009-113/000-002 WMB-Inline; for Smart Printer; on reel; plain; snap-on type	2009-113 /000-002
	Item no.: 2009-113/000-005 WMB-Inline; for Smart Printer; on reel; plain; snap-on type	2009-113 /000-005
	Item no.: 2009-113/000-006 WMB-Inline; for Smart Printer; on reel; plain; snap-on type	2009-113 /000-006
	Item no.: 2009-113/000-007 WMB-Inline; for Smart Printer; on reel; plain; snap-on type	2009-113 /000-007
	Item no.: 2009-113/000-012 WMB-Inline; for Smart Printer; on reel; plain; snap-on type	2009-113 /000-012
	Item no.: 2009-113/000-017 WMB-Inline; for Smart Printer; on reel; plain; snap-on type	2009-113 /000-017
	Item no.: 2009-113/000-023 WMB-Inline; for Smart Printer; on reel; plain; snap-on type	2009-113 /000-023
	Item no.: 2009-113/000-024 WMB-Inline; for Smart Printer; on reel; plain; snap-on type	2009-113 /000-024



Item no.: 2009-191

2009-191

Group marker carrier



Item no.: 793-3501

793-3501

WMB marking card; as card; plain; snap-on type

check



Item no.: 2000-510

2000-510

TOPJOB®S L-type test plug module; modular; for jumper contact slot



Item no.: 2000-552

2000-552

Modular TOPJOB®S connector; modular; for jumper contact slot; 2-pole



Item no.: 2000-553

2000-553

Modular TOPJOB®S connector; modular; for jumper contact slot; 3-pole



Item no.: 2000-554

2000-554

Modular TOPJOB®S connector; modular; for jumper contact slot; 4-pole



Item no.: 2000-555

2000-555

Modular TOPJOB®S connector; modular; for jumper contact slot; 5-pole



Item no.: 2000-556

2000-556

Modular TOPJOB®S connector; modular; for jumper contact slot; 6-pole



Item no.: 2000-557

2000-557

Modular TOPJOB®S connector; modular; for jumper contact slot; 7-pole



Item no.: 2000-558

2000-558

Modular TOPJOB®S connector; modular; for jumper contact slot; 8-pole



Item no.: 2000-559

2000-559

Modular TOPJOB®S connector; modular; for jumper contact slot; 9-pole



Item no.: 2000-560

2000-560

Modular TOPJOB®S connector; modular; for jumper contact slot; 10-pole



Item no.: 2009-174

2009-174

Test plug adapter; for 4 mm Ø test plugs; for testing TOPJOB®S rail-mounted terminal blocks



Item no.: 2009-182

2009-182

Testing tap; for max. 2.5 mm²; tool-free connection for individual test wires 0.08 - 2.5 mm

Item no.: 210-136

210-136

Test plug; 2 mm Ø; with 500 mm cable



Item no.: 210-137

210-137

Test plug; 2.3 mm Ø; with 500 mm cable

ferrule



Item no.: 216-241

216-241

Ferrule; Sleeve for 0.5 mm² / 20 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90

Item no.: 216-242

216-242

Ferrule; Sleeve for 0.75 mm² / 18 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90

Item no.: 216-243

216-243

Ferrule; Sleeve for 1 mm² / AWG 18; insulated; electro-tin plated; electrolytic copper; gastight



crimped; acc. to DIN 46228, Part 4/09.90

End plate



Item no.: 2000-5391

End and intermediate plate; 1 mm thick; for 3-conductor terminal blocks

5391

2000-

Jumper



Item no.: 2000-402

Push-in type jumper bar; insulated; 2-way; Nominal current 14 A

2000-402



Item no.: 2000-402/000-005

Push-in type jumper bar; insulated; 2-way; Nominal current 14 A

/000-005

2000-402



Item no.: 2000-402/000-006

Push-in type jumper bar; insulated; 2-way; Nominal current 14 A

/000-006

2000-402



Item no.: 2000-402/000-018

Push-in type jumper bar; insulated; 2-way; Nominal current 14 A

/000-018

2000-402



Item no.: 2000-403

Push-in type jumper bar; insulated; 3-way; Nominal current 14 A

2000-403



Item no.: 2000-403/000-005

Push-in type jumper bar; insulated; 3-way; Nominal current 14 A

/000-005

2000-403



Item no.: 2000-403/000-006

Push-in type jumper bar; insulated; 3-way; Nominal current 14 A

/000-006

2000-403



Item no.: 2000-404

Push-in type jumper bar; insulated; 4-way; Nominal current 14 A

2000-404



Item no.: 2000-404/000-005

Push-in type jumper bar; insulated; 4-way; Nominal current 14 A

/000-005

2000-404



Item no.: 2000-404/000-006

Push-in type jumper bar; insulated; 4-way; Nominal current 14 A

/000-006

2000-404



Item no.: 2000-405

Push-in type jumper bar; insulated; 5-way; Nominal current 14 A

2000-405



Item no.: 2000-405/000-005

Push-in type jumper bar; insulated; 5-way; Nominal current 14 A

/000-005

2000-405



Item no.: 2000-405/000-006

Push-in type jumper bar; insulated; 5-way; Nominal current 14 A

/000-006

2000-405



Item no.: 2000-405/011-000
Star point jumper; insulated; 3-way (1-3-5); IN = IN terminal block

2000-405

/011-000



Item no.: 2000-406
Push-in type jumper bar; insulated; 6-way; Nominal current 14 A

2000-406



Item no.: 2000-406/000-005
Push-in type jumper bar; insulated; 6-way; Nominal current 14 A

2000-406

/000-005



Item no.: 2000-406/000-006
Push-in type jumper bar; insulated; 6-way; Nominal current 14 A

2000-406

/000-006



Item no.: 2000-406/020-000
Delta jumper; insulated; 1-2 3-4 5-6; IN = IN terminal block

2000-406

/020-000



Item no.: 2000-407
Push-in type jumper bar; insulated; 7-way; Nominal current 14 A

2000-407



Item no.: 2000-407/000-005
Push-in type jumper bar; insulated; 7-way; Nominal current 14 A

2000-407

/000-005



Item no.: 2000-407/000-006
Push-in type jumper bar; insulated; 7-way; Nominal current 14 A

2000-407

/000-006



Item no.: 2000-408
Push-in type jumper bar; insulated; 8-way; Nominal current 14 A

2000-408



Item no.: 2000-408/000-005
Push-in type jumper bar; insulated; 8-way; Nominal current 14 A

2000-408

/000-005



Item no.: 2000-408/000-006
Push-in type jumper bar; insulated; 8-way; Nominal current 14 A

2000-408

/000-006



Item no.: 2000-409
Push-in type jumper bar; insulated; 9-way; Nominal current 14 A

2000-409



Item no.: 2000-409/000-005
Push-in type jumper bar; insulated; 9-way; Nominal current 14 A

2000-409

/000-005



Item no.: 2000-409/000-006
Push-in type jumper bar; insulated; 9-way; Nominal current 14 A

2000-409

/000-006



Item no.: 2000-410
Push-in type jumper bar; insulated; 10-way; Nominal current 14 A



2000-410



Item no.: 2000-410/000-005
Push-in type jumper bar; insulated; 10-way; Nominal current 14 A

2000-410

/000-005

	Item no.: 2000-410/000-006 Push-in type jumper bar; insulated; 10-way; Nominal current 14 A	2000-410
	Item no.: 2000-433 Push-in type jumper bar; insulated; from 1 to 3; Nominal current 14 A	2000-433
	Item no.: 2000-433/000-005 Push-in type jumper bar; insulated; from 1 to 3; Nominal current 14 A	2000-433
	Item no.: 2000-433/000-006 Push-in type jumper bar; insulated; from 1 to 3; Nominal current 14 A	2000-433
	Item no.: 2000-434 Push-in type jumper bar; insulated; from 1 to 4; Nominal current 14 A	2000-434
	Item no.: 2000-435 Push-in type jumper bar; insulated; from 1 to 5; Nominal current 14 A	2000-435
	Item no.: 2000-436 Push-in type jumper bar; insulated; from 1 to 6; Nominal current 14 A	2000-436
	Item no.: 2000-437 Push-in type jumper bar; insulated; from 1 to 7; Nominal current 14 A	2000-437
	Item no.: 2000-438 Push-in type jumper bar; insulated; from 1 to 8; Nominal current 14 A	2000-438
	Item no.: 2000-439 Push-in type jumper bar; insulated; from 1 to 9; Nominal current 14 A	2000-439
	Item no.: 2000-440 Push-in type jumper bar; insulated; from 1 to 10; Nominal current 14 A	2000-440
	Item no.: 2009-402 Push-in type wire jumper; insulated; wire length 60 mm; Conductor cross section 0.75 mm²; suitable for 2000 and 2020 Series rail-mounted terminal blocks	2009-402
	Item no.: 2009-404 Push-in type wire jumper; insulated; wire length 110 mm; Conductor cross section 0.75 mm²; suitable for 2000 and 2020 Series rail-mounted terminal blocks	2009-404
	Item no.: 2009-406 Push-in type wire jumper; insulated; wire length 250 mm; Conductor cross section 0.75 mm²; suitable for 2000 and 2020 Series rail-mounted terminal blocks	2009-406
	Item no.: 210-103 Wire commoning chain; insulated; 50 connections	210-103
	Item no.: 210-123 Wire commoning chain; insulated; 50 connections	210-123
General accessories		
	Item no.: 2000-121 Adaptor	2000-121
tools		
	Item no.: 210-647 Operating tool with partially insulated shaft; Blade (2.5 x 0.4) mm; short	210-647

**Item no.: 210-648**

Operating tool with partially insulated shaft; Blade (2.5 x 0.4) mm; short; angled

210-648

Item no.: 210-719

Operating tool with partially insulated shaft; Type 1, blade (2.5 x 0.4) mm

210-719

Protective Warning Marker**Item no.: 2000-115**

Protective warning marker; with high-voltage symbol, black; for 5 terminal blocks

2000-115

Downloads**Documentation****Bid Text**

2000-5311

docx
15.2 kB

Download

Additional Informationpdf
2.1 MB

Download

CAD/CAE - Smart Data**CAD data**

3D Download 2000-5311

URL

Download

Subject to changes.