





RoHS Compliant

BOMcheck.net

Color:

## Item description

- Allow MCS Female Connectors fitted with wire harness or cable assembly to be plugged together
- Adapter for DIN-35 rail mounting
- Coding via coding keys on both sides

## Safety information 1:

The *MULTI CONNECTION SYSTEM (MCS)* is designed without breaking capacity for compliance with DIN EN 61984. When used as intended, MCS Connectors shall not be connected/disconnected when live or under load. The circuit design should ensure header pins, which can be touched, are not live when unmated.

## Data

### Electrical data

### Ratings per IEC/EN 60664-1

Ratings note

Notice: Male connectors shall not be live when disconnected!



|                                 |       |
|---------------------------------|-------|
| Rated voltage (III / 3)         | 250 V |
| Rated impulse voltage (III / 3) | 4 kV  |
| Rated voltage (III / 2)         | 320 V |
| Rated impulse voltage (III / 2) | 4 kV  |
| Rated voltage (II / 2)          | 630 V |
| Rated impulse voltage (II / 2)  | 4 kV  |
| Rated current                   | 12 A  |

### Approvals per UL 1059

|                                |       |
|--------------------------------|-------|
| Rated voltage UL (Use Group B) | 300 V |
| Rated current UL (Use Group B) | 15 A  |
| Rated voltage UL (Use Group D) | 300 V |
| Rated current UL (Use Group D) | 10 A  |

### Approvals per UL 1977

|                                                 |       |
|-------------------------------------------------|-------|
| Rated voltage per UL 1977 (factory wiring only) | 600 V |
| Rated current per UL 1977 (factory wiring only) | 15 A  |

### Approvals per CSA

|                                 |       |
|---------------------------------|-------|
| Rated voltage CSA (Use Group B) | 300 V |
| Rated current CSA (Use Group B) | 15 A  |
| Rated voltage CSA (Use Group D) | 300 V |
| Rated current CSA (Use Group D) | 10 A  |

### Connection data

|                            |    |
|----------------------------|----|
| No. of poles               | 23 |
| Total number of potentials | 23 |
| Number of connection types | 1  |
| Number of levels           | 1  |

### Geometrical Data

|                                       |                       |
|---------------------------------------|-----------------------|
| Pin spacing                           | 5 mm / 0.197 inch     |
| Width                                 | 118.2 mm / 4.654 inch |
| Height from upper-edge of DIN-35 rail | 15 mm / 0.591 inch    |
| Depth                                 | 42.5 mm / 1.673 inch  |

### Mechanical data

|                  |             |
|------------------|-------------|
| Type of mounting | DIN-35 rail |
|------------------|-------------|

## Plug connection

|                                    |                          |
|------------------------------------|--------------------------|
| Contact type (pluggable connector) | Male connector/plug      |
| Connector connection type          | for pluggable connectors |
| Mismating protection               | No                       |

## Material Data

|                             |                                  |
|-----------------------------|----------------------------------|
| Color                       | gray                             |
| Material group              | I                                |
| Insulating material         | Polyamide 66 (PA 66)             |
| Flammability class per UL94 | V0                               |
| Contact material            | Electrolytic copper ( $E_{Cu}$ ) |
| Contact plating             | tin-plated                       |
| Fire load                   | 0.381 MJ                         |
| Weight                      | 19.6 g                           |

## Environmental Requirements

|                         |                 |
|-------------------------|-----------------|
| Limit temperature range | -60 ... +100 °C |
|-------------------------|-----------------|

## Commercial data

|                    |                        |
|--------------------|------------------------|
| Product Group      | 3 (Multi Conn. System) |
| Country of origin  | DE                     |
| GTIN               | 4045454339739          |
| Customs Tariff No. | 85366990990            |

## Approvals / Certificates

### Country specific Approvals

| Logo                                                                               | Approval                              | Additional Approval Text | Certificate name |
|------------------------------------------------------------------------------------|---------------------------------------|--------------------------|------------------|
|                                                                                    | CB<br>DEKRA Certification B.V.        | IEC 61984                | NL-39756         |
|  | CSA<br>DEKRA Certification B.V.       | C22.2                    | 1466354          |
|  | KEMA/KEUR<br>DEKRA Certification B.V. | EN 61984                 | 2190761.01       |

### Ship Approvals

| Logo | Approval | Additional Approval Text | Certificate name |
|------|----------|--------------------------|------------------|
|------|----------|--------------------------|------------------|



**ABS**  
 American Bureau of Shipping

-

14-  
 HG1241537-  
 PDA



**DNV GL**  
 Det Norske Veritas, Germanischer Lloyd

EN 60998

TAE000016Z

**DNV GL**  
 Det Norske Veritas, Germanischer Lloyd

-

TAE000016Z

## UL-Approvals

| Logo | Approval                      | Additional Approval Text | Certificate name |
|------|-------------------------------|--------------------------|------------------|
|      | <b>UR</b>                     | UL 1977                  | E45171           |
|      | UL International Germany GmbH |                          |                  |
|      | <b>UR</b>                     | UL 1977                  | E45171           |
|      | UL International Germany GmbH |                          |                  |

## Compatible products

### Marking accessories

|  |                                                                                      |         |
|--|--------------------------------------------------------------------------------------|---------|
|  | <b>Item no.: 210-833</b><br>Marking strips; on reel; 6 mm wide; plain; Self-adhesive | 210-833 |
|  | <b>Item no.: 210-834</b><br>Marking strips; on reel; 5 mm wide; plain; Self-adhesive | 210-834 |

### Carrier rail

|  |                                                                                                                                      |         |
|--|--------------------------------------------------------------------------------------------------------------------------------------|---------|
|  | <b>Item no.: 210-112</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm | 210-112 |
|  | <b>Item no.: 210-113</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715                  | 210-113 |
|  | <b>Item no.: 210-114</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715                   | 210-114 |
|  | <b>Item no.: 210-115</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm | 210-115 |
|  | <b>Item no.: 210-118</b><br>Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715                 | 210-118 |

**Item no.: 210-196**

Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715

210-196

**Item no.: 210-197**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715

210-197

**Item no.: 210-198**

Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715

210-198

**Item no.: 210-504**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715

210-504

**Item no.: 210-505**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715

210-505

**Item no.: 210-506**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715

210-506

**Item no.: 210-508**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715

210-508

**Coding****Item no.: 231-129**

Coding key; snap-on type

231-129

**Downloads****CAD/CAE - Smart Data****CAD data**

3D Download 232-523/007-000

URL

Download