

RoHS 
Compliant

BOMcheck.net

Data

Connection data

No. of poles	1
Number of connection types	1
Number of levels	1

Geometrical Data

Solder pin length	4.5 mm
Solder pin diameter	1 mm
Drilled hole diameter (tolerance)	1.2 ^(- ... +0.05) mm

Plug connection

Contact type (pluggable connector)	Male connector/plug
Connector connection type	for PCBs

PCB contact

PCB contact	THT
-------------	-----

Material Data

Weight	0.09 g
--------	--------

Commercial data

Country of origin	DE
-------------------	----

GTIN	4044918886017
Customs Tariff No.	85369010000

Approvals / Certificates

Country specific Approvals

Logo	Approval	Additional Approval Text	Certificate name
	CCA DEKRA Certification B.V.	EN 60998	NTR NL 7486
	CSA DEKRA Certification B.V.	C22.2	70048857
	KEMA/KEUR DEKRA Certification B.V.	EN 60998	2193300.01

Ship Approvals

Logo	Approval	Additional Approval Text	Certificate name
	ABS American Bureau of Shipping	-	18- HG1755093- PDA

UL-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	UR Underwriters Laboratories Inc.	UL 1059	E45172

Downloads

CAD/CAE - Smart Data

CAD data

3D Download 243-131	URL	Download
---------------------	-----	----------



Subject to changes.
