




Features:

- Power supply with TopBoost, PowerBoost and configurable overload behavior
- Configurable digital signal input and output, optical status indication, function keys
- Communication interface for configuration and monitoring
- Optional connection to IO-Link, EtherNet/IP, Modbus TCP or Modbus RTU
- Suitable for both parallel and series operation
- Natural convection cooling when horizontally mounted
- Pluggable connection technology
- Electrically isolated output voltage (SELV/PELV) per EN 61010-2-201/UL 61010-2-201
- Marker slot for WAGO marking cards (WMB) and WAGO marking strips

Technical data			
Input		Output	
Phases	1	Nominal output voltage $U_{o\ nom}$	DC 12 V (SELV)
Nominal input voltage $U_{i\ nom}$	1 x AC 100 ... 240 V	Default setting	DC 12 V
Input voltage range	1 x AC 90 ... 264 V; DC 130 ... 240 V	Nominal output current $I_{o\ nom}$	15 A (12 VDC)
Nominal mains frequency range	50 ... 60 Hz	Nominal output power	180 W
Input current I_i	≤ 2 A (240 VAC; nominal load)	Deviation	≤ 1 %
Inrush current	≤ 12 A (after 1 ms)	Residual ripple	≤ 70 mV (Peak-to-peak)
Power factor correction (PFC)	active	Current limitation	1.1 x $I_{o\ nom}$ (typ.)
Mains failure hold-up time	≥ 40 ms (230 VAC)	Overload behavior	TopBoost/PowerBoost/Time-limited constant current mode (other overload behaviors can be set)
		PowerBoost	DC 22.5 A (5 s)



Output	
TopBoost	up to 600 %

Signaling and Communication	
Signaling	Optical status indication (DC OK; load; warning and error states) Digital signal input and output (DI/DO)
Communication	Communication interface, can be used with WAGO USB Communication Cable (750-923), IO-Link Communication Module (2789-9080) or Modbus Communication Module (2789-9052)

Efficiency/power losses	
Power loss P _I	≤ 0.8 W (Standby); ≤ 2.3 W (No load); ≤ 14 W (230 VAC; nominal load)
Efficiency (typ.)	95.3 %

Circuit protection	
Internal fuse	T 6.3 A / 250 VAC
Backup fusing (required)	An external DC fuse is required for the DC input voltage.
Backup fusing (recommended)	16 A (for USA/Canada: 15 A)

Safety and protection	
Isolation voltage (pri.-sec., AC)	3510 V
Isolation voltage (pri.-PE, AC)	2200 V
Isolation voltage (sec.-PE)	DC 0.5 kV
Isolation voltage (sec.-signal)	DC 0.5 kV
Protection class	I
Protection type	IP20; per EN 60529
Overvoltage category	III (≤ 2000 m a.s.l.); II (> 2000 m a.s.l.)
Pollution degree	2
Transient suppression (primary)	Yes
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes
MTBF	> 1,200,000 h (per IEC 61709)

Connection data	
Connection type 1	Input/output/signaling
Connection technology	CAGE CLAMP®
WAGO connector	WAGO 721 Series
Solid conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG
Fine-stranded conductor; with insulated ferrule	2.5 ... 1.5 mm² / 12 ... 16 AWG
Fine-stranded conductor; with uninsulated ferrule	1.5 ... 0.08 mm² / 16 ... 28 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches

Physical data	
Width	70 mm / 2.756 inches
Height	130 mm / 5.118 inches
Depth from upper-edge of DIN-rail	130 mm / 5.118 inches
Note (dimensions)	Height without connector Height with connector: 166 mm



Mechanical Data	
Mounting type	DIN-35 rail

Material Data	
Fire load	0 MJ
Weight	1000 g

Environmental requirements	
Ambient temperature (operation at U _N)	-25 ... +70 °C (Device starts at -40 °C (type-tested))
Surrounding air temperature (storage)	-40 ... +85 °C
Relative humidity	5 ... 96 % (no condensation permissible)
Derating	See instruction leaflet
Operating altitude (max.)	5000 m

Standards and specifications	
Conformity marking	CE
Standards/specifications	EN 61010-1 EN 61010-2-201 EN 61204-3 UL 61010-1 UL 61010-2-201

Commercial data	
ETIM 8.0	EC002540
ETIM 7.0	EC002540
PU (SPU)	1 pcs
Country of origin	CN
GTIN	4066966121377
Customs tariff number	85044083900

Approvals / Certificates	
General approvals	Approvals for hazardous areas



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc.	UL 61010-2-201	E255817



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc. (HAZARDOUS LOCA- TIONS)	UL 121201	E198726

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2787-2135

↓

Documentation

Manual

Product Manual Power supply; Pro 2; 1-phase; 12 VDC output voltage; 15 A output current;

V 1.0.2
18.02.2022

pdf
8158.38 KB

↓

Bid Text

2787-2135

11.05.2022

xml
8.66 KB

↓

2787-2135

11.05.2022

docx
32.29 KB

↓

Instruction Leaflet

Power supply; Pro 2; 1-phase; 12 VDC output voltage; 15 A output current;

V 1.0.0
03.05.2021

pdf
4316.21 KB

↓

CAD/CAE-Data

CAD data

2D/3D Models 2787-2135

↓

Runtime Software

Firmware

2787-2135, Stromversorgung; Pro 2

V 010513
13.10.2021

zip
987.13 KB

↓

1 Compatible Products

1.1 Optional Accessories

1.1.1 Communication

1.1.1.1 Communication module



Item No.: 2789-9080
Communication module; IO-Link; communication capability



Item No.: 2789-9015
Communication module; Modbus RTU; RJ45; communication capability



Item No.: 2789-9052
Communication module; Modbus TCP; communication capability