




289-177



RoHS 
Compliant

[BOMcheck.net](https://www.bomcheck.net)

**Data****Electrical data**

Operating voltage	$\leq$ AC 35 V; $\leq$ DC 50 V
Nominal current	2.1 A
Insulation resistance	$\geq$ 500 M Ω
Specialty functions	With power contacts, cross-over

Safety and protection:

Dielectric strength contact-contact (AC, 1 min)	1 kVrms
---	---------

Connection data

No. of poles	10
Connection type (1)	System
No. of poles 1	10
Pluggable connector	RJ-45 shielded; with two additional power jumper contacts
Connection type (2)	System
No. of poles 2	10
Pluggable connector 2	RJ-45 shielded; with two additional power jumper contacts
Mating cycles	1000
Max. transmission length	100 m
Connecting cable	min. Cat. 5

Geometrical Data

Width	30 mm / 1.181 inch
Height from upper-edge of DIN-35 rail	51 mm / 2.008 inch
Depth	85 mm / 3.346 inch

Mechanical data

Type of mounting	DIN-35 rail
Housing design	Mounting carrier

Material Data

Fire load	0 MJ
Weight	34.3 g

Environmental Requirements

Surrounding air (operating) temperature	-40 ... 85 °C
Surrounding air (storage) temperature	-40 ... 85 °C
Relative humidity	≤ 85% (non condensing)

Commercial data

Product Group	6 (Interface Electronics)
Country of origin	DE
GTIN	4045454326135
Customs Tariff No.	85369010000

Compatible products

Marking accessories

	Item no.: 709-177 Marking strips; on reel; 7.5 mm wide; not stretchable; plain; snap-on type	709-177
	Item no.: 709-178 Marking strips; on reel; 7.5 mm wide; not stretchable; plain; snap-on type	709-178
	Item no.: 709-196 Marking strips; for laser printer	709-196
	Item no.: 709-198 Marking strips	709-198

Downloads

Documentation

Bid Text

289-177

Interface Bausteine

Apr 4, 2012


doc
21.5 kB[Download](#)**Additional Information**

Disposal; Electrical and electronic equipment, Packaging

V 1.0.0

pdf
265.8 kB[Download](#)**CAD/CAE - Smart Data****CAD data**

3D Download 289-177

[URL](#)[Download](#)

Subject to changes.