



Color coding per VDE 0293 (DIN 41651)	34-pole plug connector
White	1
Black	2
Green	3
Yellow	4
Grey	5
Blue	6
Red	7
Black	8
White	9
Black	10
Green	11
Black	12
White	13
Black	14
White	15
Black	16
White	17
Black	18
White	19
Black	20
White	21
Black	22
White	23
Black	24
White	25
Black	26
White	27
Black	28
White	29
Black	30
White	31
Black	32
White	33
Black	34

Similar to illustration

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Electrical data	
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	1 A

Connection data	
Cable type	LiYY
Color code	per DIN VDE 47100
Connection 1	
Connector	Pluggable connector per DIN 41651; female connector
Pole number 1	34
Connection type 1	System
Wire cross-section	0.14 mm²
Connection type	Pluggable Connector per DIN 41651

Connection 2	
Connector 2	open-ended
Connection type 2	open-ended

Physical data	
Cable length	1 m



Material Data	
Fire load	0 MJ
Weight	180 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	FR
GTIN	4050821777748
Customs tariff number	85444290900

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
706-100/334-100