



Similar to illustration

Color coding acc. to DIN VDE 47100		9 poles male Sub-D connector
		Pin number
White		1
Brown		2
Green		3
Yellow		4
Grey		5
Pink		6
Blue		7
Red		8
Black		9
Shield		Connected to Sub-D

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data	
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data		
Cable type	LiYCY	Connection 1 ConnectorD-subminiature male connector Pole number 19 Connection type 1System Wire cross-section0.25 mm² Connection typeD-subminiature
Color code	per DIN VDE 47100	

Connection 2	
Connector 2	open-ended
Connection type 2	open-ended

Physical data	
Cable length	3 m



Material Data	
Fire load	0 MJ
Weight	1500 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4055143651660
Customs tariff number	85444290900

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
706-100/509-300