



Conductor coding according to DIN EN 60754-2	37-pole male cable (37 conductors) Pole number
White	1
Black	2
Green	3
Yellow	4
Blue	5
Pink	6
Brown	7
Red	8
Grey	9
Orange	10
Light Blue	11
Dark Blue	12
White-Black	13
White-Blue	14
White-Red	15
White-Green	16
White-Orange	17
White-Pink	18
White-Brown	19
White-Red	20
White-Black	21
White-Blue	22
White-Red	23
White-Black	24
White-Blue	25
White-Red	26
White-Black	27
White-Blue	28
White-Red	29
White-Black	30
White-Blue	31
White-Red	32
White-Black	33
White-Blue	34
White-Red	35
White-Black	36
White-Blue	37
Blank	Discontinued in Part II

Similar to illustration

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data	
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data	
Cable type	LiYCY
Color code	per DIN VDE 47100
Connection 1	
Connector	D-subminiature male connector
Pole number 1	37
Connection type 1	System
Wire cross-section	0.25 mm²
Connection type	D-subminiature

Connection 2	
Connector 2	open-ended
Connection type 2	open-ended

Physical data	
Cable length	1 m



Material Data	
Fire load	0 MJ
Weight	1.1 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	FR
GTIN	4050821835523

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance	↓
706-100/537-300	