



Similar to illustration

Color coding acc. to DIN VDE 47100		15 poles female Sub-D connector	
		Pin number	
White			1
Brown			2
Green			3
Yellow			4
Gray			5
Pink			6
Blue			7
Red			8
Black			9
Violet			10
Gray-Pink			11
Red-Blue			12
White-Green			13
Brown-Green			14
White-Yellow			15
Shield			Connected to Sub-D

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data	
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data			
Cable type	LiYCY	Connection 1	
Color code	per DIN VDE 47100	Connector	D-subminiature female connector
		Pole number 1	15
		Connection type 1	System
		Wire cross-section	0.25 mm²
		Connection type	D-subminiature

Connection 2	
Connector 2	open-ended
Connection type 2	open-ended

Physical data	
Cable length	3 m



Material Data	
Fire load	0 MJ
Weight	1.1 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	FR
GTIN	4050821835639
Customs tariff number	85444290900

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance	↓
706-100/615-300	