

Data Sheet | Item Number: 706-2400/403-200
System cable; for Siemens S7-400; 8 analog inputs (voltage), var. 1; Length: 2 m;
Conductor cross-section: 0.25 mm²
<https://www.wago.com/706-2400/403-200>



Similar to illustration

Color coding acc. to DIN VDE 47100	25 pole Sub-D connector		PLC connector	
	Pole number	Wiring	Pole number	Signal
White	1	IN0+	9	MD+
Brown	2	IN0-	12	MD-
Green	3	IN1+	14	MD1+
Yellow	4	IN1-	17	MD1-
Grey	5	IN2+	19	MD2+
Pink	6	IN2-	22	MD2-
Blue	7	IN3+	24	MD3+
Red	8	IN3-	27	MD3-
Black	9	IN4+	29	MD4+
Violet	10	IN4-	32	MD4-
Grey-Pink	11	IN5+	34	MD5+
Red-Blue	12	IN5-	37	MD5-
White-Green	13	IN6+	39	MD6+
Brown-Green	14	IN6-	42	MD6-
White-Yellow	15	IN7+	44	MD7+
Yellow-Brown	16	IN7-	47	MD7-
White-Gray	17	IO	NC	NC
Grey-Brown	18	IO	NC	NC
White-Pink	19	IO	NC	NC
Pink-Brown	20	IO	NC	NC
White-Blue	21	IO	NC	NC
Brown-Blue	22	IO	NC	NC
White-Red	23	IO	NC	NC
Brown-Red	24	IO	NC	NC
White-Black	25	IO	NC	NC
Shield				Connected to Sub-D

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data	
Inputs/outputs	8 analog inputs; voltage
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Compatibility	
Siemens	
Siemens S7-400	6ES7 431-7KF00-0AB0

Connection data	
Cable type	LiYCY
Color code	per DIN VDE 47100
Connection 1	
Connector	D-subminiature female connector
Pole number 1	25
Connection type 1	System
Wire cross-section	0.25 mm²

Connection 2	
Connector 2	Siemens 6ES7-492-1BL00-0AA0
Pole number 2	48
Connection type 2	System



Physical data	
Cable length	2 m

Material Data	
Fire load	0 MJ
Weight	1.1 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	Box
GTIN	4055143038423

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 706-2400/403-200	

Documentation

System Description	
WAGO System Wiring, Selection Guide	pdf 533.15 KB 