



Similar to illustration

Color coding acc. to DIN VDE 47100	25 pole Sub-D connector		PLC connector	
	Pole number	Wiring	Pole number	Signal
White	1	IN0+	3	IN0+
Brown	2	IN0-	3	IN0-
Green	3	IN1+	13	IN1+
Yellow	4	IN1-	14	IN1-
Grey	5	IN2+	18	IN2+
Pink	6	IN2-	19	IN2-
Blue	7	IN3+	23	IN3+
Red	8	IN3-	24	IN3-
Black	9	IN4+	30	IN4+
Violet	10	IN4-	31	IN4-
Grey-Pink	11	IN5+	35	IN5+
Red-Blue	12	IN5-	36	IN5-
White-Green	13	IN6+	40	IN6+
Brown-Green	14	IN6-	41	IN6-
White-Yellow	15	IN7+	45	IN7+
Yellow-Brown	16	IN7-	46	IN7-
White-Grey	17	IN	47	IN
Grey-Brown	18	-	26	Maup
White-Pink	19	IN	48	IN
Pink-Brown	20	IN	49	IN
White-Blue	21	IN	50	IN
Brown-Blue	22	IN	51	IN
White-Red	23	IN	52	IN
Brown-Red	24	IN	53	IN
White-Black	25	IN	54	IN
Shield				Connected to Sub-D

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data	
Inputs/outputs	8 analog inputs; current
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Compatibility	
Siemens	
Siemens S7-400	6ES7 431-7KF00-0AB0

Connection data	
Cable type	LiYCY
Color code	per DIN VDE 47100
Connection 1	
Connector	D-subminiature female connector
Pole number 1	25
Connection type 1	System
Wire cross-section	0.25 mm²

Connection 2	
Connector 2	Siemens 6ES7-492-1BL00-0AA0
Pole number 2	48
Connection type 2	System



Physical data	
Cable length	3 m

Material Data	
Fire load	0 MJ
Weight	684 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	FR
GTIN	4050821646471

Downloads	
-----------	--

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 706-2400/404-300	

Documentation	
System Description	
WAGO System Wiring, Selection Guide	pdf 533.15 KB 