

Data sheet | Item number: 706-2500/402-100

System cable; for Siemens S7-1500; 4 analog inputs (current); Length: 1 m;
Conductor cross-section: 0.25 mm²

www.wago.com/706-2500_402-100



Item description

Note:

When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Data

Electrical data

Inputs/outputs	4 analog inputs; current
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	1 A

Connection data

Compatible PLC Modules	Siemens S7-1500
Compatible PLC I/O Card Types	6ES7 531-7QD00-0AB0
Connection type (1)	System
Pole number 1	25
Pluggable connectors	D-sub female connector
Connection type 2	System
Pole number 2	40
Connector 2	Siemens 6ES7-592-1BM00-0XB0
Cable type	LIYCY
Wire cross-section	0.14 mm ²
Color code	per DIN VDE 47100

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.

Physical data

Cable length	1 m
--------------	-----

Material data

Weight	367 g
--------	-------

Environmental requirements

Surrounding air temperature (operation)	-20 ... 50 °C
---	---------------

Commercial data

Packaging type	bag
Country of origin	FR
GTIN	4055143402842
Customs tariff number	85444290900

Downloads

Documentation

System Description

WAGO System Wiring, Selection Guide

This guide will help you select the appropriate interface modules and system cables for the controller you are using.

pdf
545.9 kB

[Download](#)

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-2500/402-100

System cable; for Siemens S7-1500; 4 analog inputs (current); Length: 1 m;
Conductor cross-section: 0.25 mm²

[URL](#)

[Download](#)

Installation Notes

Subject to changes. Please also observe the further product documentation!