

## Data sheet | Item number: 706-3037/401-100

System cable; for Schneider TSX; 8 analog inputs; Length: 1 m; Conductor cross-section: 0.25 mm<sup>2</sup>

[www.wago.com/706-3037\\_401-100](http://www.wago.com/706-3037_401-100)



### Item description

#### Note:

When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

### Data

#### Electrical data

|                         |                 |
|-------------------------|-----------------|
| Inputs/outputs          | 8 analog inputs |
| Operating voltage       | ≤ AC/DC 35 V    |
| Current per wire (max.) | 2 A             |

### Connection data

|                               |                            |
|-------------------------------|----------------------------|
| Compatible PLC Modules        | Schneider TSX              |
| Compatible PLC I/O Card Types | TSX AEZ 801<br>TSX AEZ 802 |

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.



|                      |                        |
|----------------------|------------------------|
| Connection type (1)  | System                 |
| Pole number 1        | 25                     |
| Pluggable connectors | D-sub female connector |
| Connection type 2    | System                 |
| Pole number 2        | 15                     |
| Connector 2          | Schneider TSXBLZH01    |
| Cable type           | LiYCY                  |
| Wire cross-section   | 0.25 mm²               |
| Color code           | per DIN VDE 47100      |

## Physical data

|              |     |
|--------------|-----|
| Cable length | 1 m |
|--------------|-----|

## Material data

|        |       |
|--------|-------|
| Weight | 252 g |
|--------|-------|

## Environmental requirements

|                                         |               |
|-----------------------------------------|---------------|
| Surrounding air temperature (operation) | -20 ... 50 °C |
|-----------------------------------------|---------------|

## Commercial data

|                       |               |
|-----------------------|---------------|
| Packaging type        | bag           |
| Country of origin     | FR            |
| GTIN                  | 4055143999069 |
| Customs tariff number | 8544429090    |

## Downloads

### Documentation

#### System Description

WAGO System Wiring, Selection Guide

This guide will help you select the appropriate interface modules and system cables for the controller you are using.

pdf  
545.9 kB

[Download](#)

## Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.