

Data Sheet | Item Number: 706-3037/500-300

System cable; for Schneider TSX; 4 analog outputs; Length: 3 m; Conductor cross-section: 0.25 mm²

<https://www.wago.com/706-3037/500-300>



Similar to illustration

Color coding acc. to DIN VDE 47100	15 poles Sub-D connector		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	OUT0+	1	0+
Brown	2	OUT0-	2	0-
Green	3	OUT1+	5	1+
Yellow	4	OUT1-	6	1-
Grey	5	OUT2+	9	2+
Pink	6	OUT2-	10	2-
Blue	7	OUT3+	13	3+
Red	8	OUT3-	14	3-
Black	9	nc	nc	nc
Violet	10	nc	nc	nc
Grey-Pink	11	nc	nc	nc
Red-Blue	12	nc	nc	nc
White-Green	13	nc	nc	nc
Brown-Green	14	nc	nc	nc
White-Yellow	15	nc	nc	nc
Shield		Connected to Sub-D		

Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.
------	---

Electrical data

Inputs/outputs	4 analog outputs
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Compatibility

Schneider

Schneider TSX	TSX ASZ 200 TSX ASZ 401
---------------	----------------------------

Connection data

Cable type	LiYCY	Connection 1	
Color code	per DIN VDE 47100	Connector	D-subminiature female connector
		Pole number 1	15
		Connection type 1	System
		Wire cross-section	0.25 mm ²

Connection 2

Connector 2	Schneider TSXBLZH01
Pole number 2	15
Connection type 2	System



Physical data	
Cable length	3 m

Material Data	
Fire load	0 MJ
Weight	1.1 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	Box
GTIN	4055143037822

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 706-3037/500-300	

Documentation

System Description	
WAGO System Wiring, Selection Guide	pdf 533.15 KB 