



Similar to illustration

Color coding acc. to DIN VDE 47100 Cable 1: Channel 0-7	Connector WAGO 231 L/R		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	OUT0.0	1	0
Brown	2	OUT0.1	3	1
Green	3	OUT0.2	3	2
Yellow	4	OUT0.3	4	3
Grey	5	OUT0.4	6	4
Pink	6	OUT0.5	7	5
Blue	7	OUT0.6	8	6
Red	8	OUT0.7	8	7
Black	9	L	1+10	PS-15
Violet	10	nc	nc	nc

Color coding acc. to DIN VDE 47100 Cable 2: Channel 8-15	Connector WAGO 231 L/R		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	11	OUT1.0	11	8
Brown	12	OUT1.1	12	9
Green	13	OUT1.2	13	10
Yellow	14	OUT1.3	14	11
Grey	15	OUT1.4	16	12
Pink	16	OUT1.5	17	13
Blue	17	OUT1.6	18	14
Red	18	OUT1.7	19	15
Black	19	nc	10	nc
Violet	20	nc	nc	nc

Notes	
Note	If less than 3 channels are used simultaneously, the maximum current per conductor is 2 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L. If more than 3 channels are used simultaneously, the maximum current per conductor is 0.75 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L.

Electrical data	
Inputs/outputs	16 digital outputs; for higher voltages
Operating voltage	≤ AC/DC 250 V
Current per wire (max.)	0.75 A

Compatibility	
Schneider	
Schneider TSX	TSX DSY 08R5 TSX DSY 16R5 TSX DSY 16S4 TSX DSY 16S5

Connection data	
Cable type	LiYY
Color code	per DIN VDE 47100
Connection 1	
Connector	WAGO 231 Series
Pole number 1	10
Connection type 1	System
Wire cross-section	0.34 mm²
Connection 2	
Connector 2	WAGO 231 Series
Pole number 2	10
Connection type 2	System
Connection 3	
Connector 3	Schneider TSXBLY01
Pole number 3	20
Connection type 3	System



Physical data	
Cable length	2 m

Material Data	
Fire load	0 MJ
Weight	732 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	Bag
GTIN	4055143999168
Customs tariff number	85444290900

Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 706-3057/201-200	

Documentation	
System Description	
WAGO System Wiring, Selection Guide	pdf 533.15 KB 