

Data Sheet | Item Number: 706-3057/203-300
System cable; for Schneider TSX; 8 digital outputs for higher voltages, var. 1;
Length: 3 m; Conductor cross-section: 0.34 mm²
<https://www.wago.com/706-3057/203-300>



Similar to illustration

Color coding acc. to DIN VDE 47100	Connector WAGO 231 (JA)		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	OUT0.0	1	0
Brown	2	OUT0.1	3	1
Green	3	OUT0.2	5	2
Yellow	4	OUT0.3	7	3
Grey	5	OUT0.4	9	4
Pink	6	OUT0.5	11	5
Blue	7	OUT0.6	13	6
Red	8	OUT0.7	15	7
Black	9	L/+	16	Alim+
Violet	10	N/-	17	Alim-
Grey-Pink	11	nc	nc	nc
Red-Blue	12	nc	nc	nc

Notes	
Note	If less than 3 channels are used simultaneously, the maximum current per conductor is 2 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L. If more than 3 channels are used simultaneously, the maximum current per conductor is 0.75 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L.

Electrical data	
Inputs/outputs	8 digital outputs; for higher voltages
Operating voltage	≤ AC/DC 250 V
Current per wire (max.)	0.75 A

Compatibility	
Schneider	
Schneider TSX	TSX DSY 08T22 TSX DSY 08T31

Connection data	
Cable type	LiYY
Color code	per DIN VDE 47100
Connection 1	
Connector	WAGO 231 Series
Pole number 1	10
Connection type 1	System
Wire cross-section	0.34 mm²

Connection 2	
Connector 2	Schneider TSXBLY01
Pole number 2	20
Connection type 2	System



Physical data	
Cable length	3 m

Material Data	
Fire load	0 MJ
Weight	1.1 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	Box
GTIN	4055143037839

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 706-3057/203-300	

Documentation

System Description	
WAGO System Wiring, Selection Guide	pdf 533.15 KB 