
Data sheet | Item number: 706-3140/302-100

System cable; for Schneider Modicon Quantum; 16 digital inputs and 8 digital outputs; Length: 1 m; Conductor cross-section: 0.14 mm²



www.wago.com/706-3140_302-100



Item description

Note:

When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Data

Electrical data

Inputs/outputs	16 digital inputs and 8 digital outputs
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	1A

Connection data

Compatible PLC Modules	Schneider Modicon Quantum
Compatible PLC I/O Card Types	140 DDM 390 00
Connection type (1)	System
Pole number 1	10
Pluggable connectors	Pluggable connector per DIN 41651; Female connector
Connection type 2	System
Pole number 2	20
Connector 2	Pluggable connector per DIN 41651; Female connector
Connection type (3)	System
Pole number 3	40

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.

Data sheet | Item number: 706-3140/302-100

www.wago.com/706-3140_302-100



Connector 3	Schneider 140XTS00200
Cable type	LiYY
Wire cross-section	0.14 mm²
Color code	per DIN VDE 47100

Physical data

Cable length 1 m

Material data

Weight 351 g

Environmental requirements

Surrounding air temperature (operation) -20 ... 50 °C

Commercial data

Packaging type	bag
Country of origin	FR
GTIN	4055143999427
Customs tariff number	8544429090

Downloads

Documentation

System Description

WAGO System Wiring, Selection Guide pdf Download
This guide will help you select the appropriate interface modules and system cables 545.9 kB for the controller you are using.

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-3140/302-100

URL

System cable; for Schneider Modicon Quantum; 16 digital inputs and 8 digital

outputs; Length: 1 m; Conductor cross-section: 0.14 mm²

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.

Download

www.wago.com/706-3140_302-100

W/AGO

Installation Notes



 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.