

Data Sheet | Item Number: 706-3340/400-300
System cable; for Schneider Modicon M340; 4 analog inputs (current); Length: 3 m;
Conductor cross-section: 0.25 mm²
<https://www.wago.com/706-3340/400-300>



Similar to illustration

Color coding acc. to DIN VDE 47100	15 poles Sub-D connector		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	0+	1-3	LI0
Brown	2	0-	2	Com0
Green	3	1+	7-9	LI1
Yellow	4	1-	8	Com1
Grey	5	2+	11-13	LI2
Pink	6	2-	12	Com2
Blue	7	3+	17-19	LI3
Red	8	3-	18	Com3
Black	9	nc	nc	nc
Violet	10	nc	nc	nc
Grey-Pink	11	nc	nc	nc
Red-Blue	12	nc	nc	nc
White-Green	13	nc	nc	nc
Brown-Green	14	nc	nc	nc
White-Yellow	15	nc	nc	nc
Shield	Connected to Sub-D			

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data	
Inputs/outputs	4 analog inputs; current
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Compatibility	
Schneider	
Schneider Modicon M340	BMX AMI 0410

Connection data	
Cable type	LiYCY
Color code	per DIN VDE 47100
Connection 1	
Connector	D-subminiature female connector
Pole number 1	15
Connection type 1	System
Wire cross-section	0.25 mm²

Connection 2	
Connector 2	Schneider BMXFTB2020
Pole number 2	20
Connection type 2	System



Physical data	
Cable length	3 m

Material Data	
Fire load	0 MJ
Weight	261 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	FR
GTIN	4050821240150
Customs tariff number	85444290900

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 706-3340/400-300	

Documentation	
System Description	
WAGO System Wiring, Selection Guide	pdf 533.15 KB 