



Similar to illustration

Color coding acc. to DIN VDE 47100	25 pole Sub-D connector		PLC connector	
	Pole number	Wiring	Pole number	Signal
White	1	IN0+	1	IN0+
Brown	2	IN0-	3	IN0-
Green	3	IN1+	8	IN1+
Yellow	4	IN1-	9	IN1-
Grey	5	IN2+	9	IN2+
Pink	6	IN2-	11	IN2-
Blue	7	IN3+	12	IN3+
Red	8	IN3-	14	IN3-
Black	9	OUT4+	17	OUT+
Violet	10	OUT4-	18	OUT-
Grey-Pink	11	OUT5+	19	OUT+
Red-Blue	12	OUT5-	20	OUT-
White-Green	13	IN	NC	NC
Brown-Green	14	IN	NC	NC
White-Yellow	15	IN	NC	NC
Yellow-Brown	16	IN	NC	NC
White-Gray	17	IN	NC	NC
Grey-Brown	18	IN	NC	NC
White-Pink	19	IN	NC	NC
Pink-Brown	20	IN	NC	NC
White-Blue	21	IN	NC	NC
Brown-Blue	22	IN	NC	NC
White-Red	23	IN	NC	NC
Brown-Red	24	IN	NC	NC
White-Black	25	IN	NC	NC
Shields				Connected to Sub-D

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data	
Inputs/outputs	6 analog inputs or outputs; voltage
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Compatibility	
Schneider	
Schneider Modicon M340	BMX AMM 0600

Connection data	
Cable type	LiYCY
Color code	per DIN VDE 47100
Connection 1	
Connector	D-subminiature female connector
Pole number 1	25
Connection type 1	System
Wire cross-section	0.25 mm²

Connection 2	
Connector 2	Schneider BMXAMM0600
Pole number 2	20
Connection type 2	System



Physical data	
Cable length	2 m

Material Data	
Fire load	0 MJ
Weight	1.1 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	Box
GTIN	4045454880118

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 706-3340/501-200	

Documentation

System Description	
WAGO System Wiring, Selection Guide	pdf 533.15 KB 