

System cable; for Rockwell Compact Logix; 4 analog outputs; Length: 3 m; Conductor cross-section: 0.25 mm²



Color coding acc. to DIN VDE 47100	15 poles Sub-D connector		PLC connector	
	Pin number	Wiring	Pin number	Signal
White		1 0+	4	W/OUT
Brown		2 0-	3	Com0
Green		3 1+	8	W/OUT
Yellow		4 1-	7	Com1
Grey		5 2+	12	W/OUT
Pink		6 2-	11	Com2
Blue		7 3+	16	W/OUT
Red		8 3-	15	Com3
Black		9 nc	nc	nc
Violet		10 nc	nc	nc
Grey-Pink		11 nc	nc	nc
Red-Blue		12 nc	nc	nc
White-Green		13 nc	nc	nc
Brown-Green		14 nc	nc	nc
White-Yellow		15 nc	nc	nc
Shield		Connected to Sub-D		

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Inputs/outputs 4 analog outputs

Inputs/outputs 4 analog outputs

Operating voltage	≤ AC/DC 35 V
-------------------	--------------

Current per wire (max.) 2 A

Rockwell

Rockwell

Rockwell Compact Logix	1769 - OF4CI 1769 - OF4VI
------------------------	------------------------------

Cable type	LiCY	Connection 1
------------	------	--------------

Cable type	LiCY	Connection 1
------------	------	--------------

Color code	per DIN VDE 47100	Connector	D-sub female connector
------------	-------------------	-----------	------------------------

Connector D-sub female connector

Connector D-sub female connector

Pole number 1 15

Connection type 1	System
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

Wire cross-section	0.25 mm ²
--------------------	----------------------

Connector 2 Rockwell-RTBN18

Connector 2 Rockwell-RTBN18

Pole number 2	18
---------------	----

Connection type 2	System
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100



Physical data	
Cable length	3 m

Material Data	
Fire load	0 MJ
Weight	1.1 g

Environmental requirements	
Ambient temperature (operation at U _N)	-20 ... +50 °C

Commercial data	
ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	Box
GTIN	4055143039314

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 706-4769/501-300	

Documentation

System Description	
WAGO System Wiring, Selection Guide	pdf 533.15 KB 