


## Data sheet | Item number: 722-134

THT female header; 0.6 x 1.0 mm solder pin; straight; 100% protected against mismatching; Pin spacing 5 mm; 4-pole




722-134




RoHS Compliant

[BOMcheck.net](https://www.bomcheck.net)

Color:





### Item description

- Horizontal or vertical PCB mounting via straight or angled solder pins
- For board-to-board and board-to-wire connections
- Touch-proof PCB outputs
- Easy-to-identify PCB inputs and outputs
- 100 % protected against mismating
- With coding fingers

### Safety information 1:

The *MULTI CONNECTION SYSTEM (MCS)* is designed without breaking capacity for compliance with DIN EN 61984. When used as intended, MCS Connectors shall not be connected/disconnected when live or under load. The circuit design should ensure header pins, which can be touched, are not live when unmated.

### Data

#### Electrical data

#### Ratings per IEC/EN 60664-1

|                                 |       |
|---------------------------------|-------|
| Rated voltage (III / 3)         | 320 V |
| Rated impulse voltage (III / 3) | 4 kV  |
| Rated voltage (III / 2)         | 320 V |
| Rated impulse voltage (III / 2) | 4 kV  |

|                                |       |
|--------------------------------|-------|
| Rated voltage (II / 2)         | 630 V |
| Rated impulse voltage (II / 2) | 4 kV  |
| Rated current                  | 12 A  |

### Approvals per UL 1059

|                                |       |
|--------------------------------|-------|
| Rated voltage UL (Use Group B) | 300 V |
| Rated current UL (Use Group B) | 15 A  |
| Rated voltage UL (Use Group D) | 300 V |
| Rated current UL (Use Group D) | 10 A  |

### Approvals per UL 1977

|                                                 |       |
|-------------------------------------------------|-------|
| Rated voltage per UL 1977 (factory wiring only) | 600 V |
| Rated current per UL 1977 (factory wiring only) | 15 A  |

### Approvals per CSA

|                                 |       |
|---------------------------------|-------|
| Rated voltage CSA (Use Group B) | 300 V |
| Rated current CSA (Use Group B) | 15 A  |
| Rated voltage CSA (Use Group D) | 300 V |
| Rated current CSA (Use Group D) | 10 A  |

### Connection data

|                            |   |
|----------------------------|---|
| No. of poles               | 4 |
| Total number of potentials | 4 |
| Number of connection types | 1 |
| Number of levels           | 1 |

### Geometrical Data

|                                   |                                |
|-----------------------------------|--------------------------------|
| Pin spacing                       | 5 mm / 0.197 inch              |
| Width                             | 21.5 mm / 0.846 inch           |
| Height                            | 23.25 mm / 0.915 inch          |
| Height from the surface           | 18.25 mm / 0.719 inch          |
| Depth                             | 11.6 mm / 0.457 inch           |
| Solder pin length                 | 5 mm                           |
| Solder pin dimensions             | 0.6 x 1 mm                     |
| Drilled hole diameter (tolerance) | 1.3 <sup>(- ... +0.1)</sup> mm |

### Plug connection

|                                    |                         |
|------------------------------------|-------------------------|
| Contact type (pluggable connector) | Female connector/socket |
| Connector connection type          | for PCBs                |

|                             |     |
|-----------------------------|-----|
| Mismating protection        | Yes |
| Mating direction to the PCB | 90° |

### PCB contact

|                                     |                                           |
|-------------------------------------|-------------------------------------------|
| PCB contact                         | THT                                       |
| Solder pin arrangement              | over the entire female connector, in line |
| Number of solder pins per potential | 1                                         |

### Material Data

|                             |                      |
|-----------------------------|----------------------|
| Color                       | light gray           |
| Material group              | I                    |
| Insulating material         | Polyamide 66 (PA 66) |
| Flammability class per UL94 | V0                   |
| Contact material            | Copper alloy         |
| Contact plating             | tin-plated           |
| Fire load                   | 0.065 MJ             |
| Weight                      | 3.8 g                |

### Environmental Requirements

|                         |                |
|-------------------------|----------------|
| Limit temperature range | -60 ... +85 °C |
|-------------------------|----------------|

### Commercial data

|                    |                        |
|--------------------|------------------------|
| Product Group      | 3 (Multi Conn. System) |
| Country of origin  | DE                     |
| GTIN               | 4044918580410          |
| Customs Tariff No. | 85366990990            |

### Approvals / Certificates

#### Country specific Approvals

| Logo                                                                               | Approval                                     | Additional Approval Text | Certificate name |
|------------------------------------------------------------------------------------|----------------------------------------------|--------------------------|------------------|
|                                                                                    | <b>CB</b><br>DEKRA Certification B.V.        | IEC 61984                | NL-39756         |
|  | <b>CSA</b><br>DEKRA Certification B.V.       | C22.2                    | 1466354          |
|  | <b>KEMA/KEUR</b><br>DEKRA Certification B.V. | EN 61984                 | 2190761.01       |

## UL-Approvals

| Logo                                                                             | Approval                            | Additional Approval Text | Certificate name |
|----------------------------------------------------------------------------------|-------------------------------------|--------------------------|------------------|
|  | UR<br>UL International Germany GmbH | UL 1977                  | E45171           |
|  | UR<br>UL International Germany GmbH | UL 1977                  | E45171           |

## Compatible products

## Marking accessories

|                                                                                    |                                                                                         |         |
|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|---------|
|    | Item no.: 210-833<br>Marking strips; on reel; 6 mm wide; plain; Self-adhesive           | 210-833 |
|   | Item no.: 210-834<br>Marking strips; on reel; 5 mm wide; plain; Self-adhesive           | 210-834 |
| check                                                                              |                                                                                         |         |
|  | Item no.: 210-136<br>Test plug; 2 mm Ø; with 500 mm cable                               | 210-136 |
|  | Item no.: 210-137<br>Test plug; 2.3 mm Ø; with 500 mm cable                             | 210-137 |
|  | Item no.: 231-661<br>Test plugs for female connectors; for 5 mm and 5.08 mm pin spacing | 231-661 |

## Downloads

## CAD/CAE - Smart Data

## CAD data

|                     |     |          |
|---------------------|-----|----------|
| 3D Download 722-134 | URL | Download |
|---------------------|-----|----------|

## PCB libraries

|                                                                                                                                              |                      |               |          |
|----------------------------------------------------------------------------------------------------------------------------------------------|----------------------|---------------|----------|
| TARGET Library for WAGO Pluggable PCB Connectors (Multi-Connection System)<br>Compatible with TARGET PCB Design Software Version 17.x        | 1.1.0<br>Oct 6, 2014 | zip<br>7.4 MB | Download |
| EAGLE Library for WAGO Pluggable PCB Connectors (MULTI CONNECTION SYSTEM)<br>Compatible with EAGLE PCB Design Software Version 6.x or higher | 2.1<br>Oct 6, 2014   | zip<br>6.2 MB | Download |
| DesignSpark Library for WAGO Pluggable PCB Connectors (MULTI CONNECTION SYSTEM)                                                              | 2.1                  | zip           | Download |



Subject to changes.