







RoHS   
Compliant

[BOMcheck.net](https://www.bomcheck.net)



Item description

The supply module provides the I/O modules with the corresponding supply potential.

The maximum current at the supply module is 10A. When configuring the system, it must be ensured that this total current is not exceeded.

Should higher currents be necessary, intermediate supply modules must be added in the assembly.

Data  
Technical Data

|                                                        |                                                                        |
|--------------------------------------------------------|------------------------------------------------------------------------|
| Type of signal                                         | Voltage                                                                |
| Type of signal voltage                                 | AC/DC 0 ... 230 V                                                      |
| System supply voltage                                  | DC 5 V; via data contacts                                              |
| Field supply voltage                                   | AC/DC 230 V (-15 ... +10 %); via wiring level (CAGE CLAMP® connection) |
| Number of outgoing power jumper contacts               | 3                                                                      |
| Current carrying capacity of the power jumper contacts | 10 A                                                                   |

Connection data

Connection technology: field supply

|                         |                                  |
|-------------------------|----------------------------------|
|                         | 6 x CAGE CLAMP®                  |
| Connection type (1)     | Field supply                     |
| Solid conductor         | 0.08 ... 2.5 mm² / 28 ... 14 AWG |
| Fine-stranded conductor | 0.08 ... 2.5 mm² / 28 ... 14 AWG |
| Strip length            | 8 ... 9 mm / 0.31 ... 0.35 inch  |

## Geometrical Data

|                                       |                      |
|---------------------------------------|----------------------|
| Width                                 | 12 mm / 0.472 inch   |
| Height                                | 69.8 mm / 2.748 inch |
| Height from upper-edge of DIN-35 rail | 62.6 mm / 2.465 inch |
| Depth                                 | 100 mm / 3.937 inch  |

## Mechanical data

|                  |             |
|------------------|-------------|
| Type of mounting | DIN-35 rail |
|------------------|-------------|

## Material Data

|                    |                              |
|--------------------|------------------------------|
| Color              | light gray                   |
| Housing material   | Polycarbonate, polyamide 6.6 |
| Fire load          | 1.089 MJ                     |
| Weight             | 43.64 g                      |
| Conformity marking | 1                            |

## Environmental Requirements


|                                                                                    |                                           |
|------------------------------------------------------------------------------------|-------------------------------------------|
| Surrounding air (operating) temperature                                            | 0 ... 55 °C                               |
| Surrounding air (storage) temperature                                              | -40 ... 85 °C                             |
| Protection class                                                                   | IP20                                      |
| Degree of pollution (5)                                                            | 2 per IEC 61131-2                         |
| Operating altitude                                                                 | 0 ... 2000 m                              |
| Mounting position                                                                  | horizontal (standing/lying) or vertical   |
| Relative air humidity (no condensation)                                            | 95 %                                      |
| Vibration resistance                                                               | 4g per IEC 60068-2-6                      |
| Shock resistance                                                                   | 15g per IEC 60068-2-27                    |
| EMC immunity to interference                                                       | acc. to EN 61000-6-2, marine applications |
| EMC emission of interference                                                       | acc. to EN 61000-6-4, marine applications |
| Exposure to pollutants                                                             | Per IEC 60068-2-42 and IEC 60068-2-43     |
| Permissible H <sub>2</sub> S contaminant concentration at a relative humidity 75 % | 10 ppm                                    |
| Permissible SO <sub>2</sub> contaminant concentration at a relative humidity 75 %  | 25 ppm                                    |

## Commercial data

|                    |                 |
|--------------------|-----------------|
| Product Group      | 15 (Remote I/O) |
| Country of origin  | DE              |
| GTIN               | 4045454393793   |
| Customs Tariff No. | 85389091890     |

## Approvals / Certificates

## Ex-Approvals

| Logo                                                                              | Approval                                                   | Additional Approval Text | Certificate name                  |
|-----------------------------------------------------------------------------------|------------------------------------------------------------|--------------------------|-----------------------------------|
|   | ATEX<br>TUEV Nord Cert GmbH                                | EN 60079-0               | TÜV 07<br>ATEX<br>554086 X<br>en. |
|   | TUEV Nord<br>TUEV Nord Cert GmbH                           | IEC 60079-0              | IECEX<br>TUN<br>09.0001 X         |
|  | UL<br>Underwriters Laboratories Inc. (HAZARDOUS LOCATIONS) | ANSI/ISA 12.12.01        | E198726<br>Sec.1                  |

## Country specific Approvals

| Logo                                                                               | Approval                             | Additional Approval Text | Certificate name            |
|------------------------------------------------------------------------------------|--------------------------------------|--------------------------|-----------------------------|
|  | KC<br>National Radio Research Agency | Article 58-2, Clause 3   | MSIP-<br>REM-W43-<br>SPP750 |

## Ship Approvals

| Logo                                                                                | Approval                                         | Additional Approval Text | Certificate name |
|-------------------------------------------------------------------------------------|--------------------------------------------------|--------------------------|------------------|
|   | ABS<br>American Bureau of Shipping               | -                        | 19-<br>HG1821926 |
|  | BV<br>Bureau Veritas S.A.                        | -                        | 13453/DO BV      |
|   | DNV GL<br>Det Norske Veritas, Germanischer Lloyd | -                        | TAA0000194       |

|                                                                                   |                                          |   |                       |
|-----------------------------------------------------------------------------------|------------------------------------------|---|-----------------------|
|   | <b>KR</b><br>Korean Register of Shipping | - | HMB05880-AC001        |
|  | <b>LR</b><br>Lloyds Register             | - | 02/20026 (E5)         |
|   | <b>NK</b><br>Nippon Kaiji Kyokai         | - | TA17255M              |
|  | <b>PRS</b><br>Polski Rejestr Statków     | - | TE/2236<br>/880590/19 |
|   | <b>RINA</b><br>RINA Germany GmbH         | - | ELE134212XG           |

#### UL-Approvals


| Logo                                                                               | Approval                                                            | Additional Approval Text | Certificate name |
|------------------------------------------------------------------------------------|---------------------------------------------------------------------|--------------------------|------------------|
|  | <b>UL</b><br>UL International Netherlands B.V. (ORDINARY LOCATIONS) | UL 508                   | E175199<br>Sec.1 |

#### Compatible products

##### system box


|                                                                                    |                                                                                                                                     |         |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|---------|
|  | <b>Item no.: 850-804</b><br>IP65 enclosure; Stainless steel; WxHxD (400x123x200 mm); 4 x M20, 16 x M16, 28 x M12 cable grip         | 850-804 |
|  | <b>Item no.: 850-804/000-001</b><br>IP65 enclosure; Stainless steel; WxHxD (400x123x200 mm); 2 x M20, 13 x M16, 32 x M12 cable grip | 850-804 |
|  | <b>Item no.: 850-805</b><br>IP65 enclosure; Stainless steel; WxHxD (600x123x200 mm); 4 x M20, 19 x M16, 67 x M12 cable grip         | 850-805 |
|  | <b>Item no.: 850-814/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (200x120x200 mm); without flange plate            | 850-814 |

|                                                                                    |                                                                                                                                          |                     |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
|    | <b>Item no.: 850-815/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (300x120x200 mm); without flange plate                 | 850-815<br>/002-000 |
|    | <b>Item no.: 850-816/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (400x120x200 mm); without flange plate                 | 850-816<br>/002-000 |
|    | <b>Item no.: 850-817/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (600x120x200 mm); without flange plate                 | 850-817<br>/002-000 |
|    | <b>Item no.: 850-825</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (160x100x160 mm); 9 x M12, 4 x M20                               | 850-825             |
|    | <b>Item no.: 850-826</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip          | 850-826             |
|    | <b>Item no.: 850-826/002-000</b><br>IP65 enclosure; Aluminium (RAL 7035); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip  | 850-826<br>/002-000 |
|    | <b>Item no.: 850-827</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip          | 850-827             |
|   | <b>Item no.: 850-827/002-000</b><br>IP65 enclosure; Aluminium (RAL 7035); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip  | 850-827<br>/002-000 |
|  | <b>Item no.: 850-828</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip         | 850-828             |
|  | <b>Item no.: 850-828/002-000</b><br>IP65 enclosure; Aluminium (RAL 7035); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip | 850-828<br>/002-000 |
|  | <b>Item no.: 850-834</b><br>IP65 enclosure; Polyester (RAL 7032); WxHxD (164x100x164 mm); 9 x M12, 4 x M20                               | 850-834             |
|  | <b>Item no.: 850-835</b><br>IP65 enclosure; Polyester (RAL 7032); WxHxD (244x100x164 mm); 4 x M20, 4 x M16, 14 x M12 cable grip          | 850-835             |
|  | <b>Item no.: 850-836</b><br>IP65 enclosure; Polyester (RAL 7032); WxHxD (324x100x164 mm); 4 x M20, 8 x M16, 17 x M12 cable grip          | 850-836             |
| <b>Carrier rail</b>                                                                |                                                                                                                                          |                     |
|  | <b>Item no.: 210-112</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm     | 210-112             |
|  | <b>Item no.: 210-113</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715                      | 210-113             |
|  | <b>Item no.: 210-114</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715                       | 210-114             |
|                                                                                    | <b>Item no.: 210-115</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm     | 210-115             |

**Item no.: 210-118**

Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715

210-118

**Item no.: 210-196**

Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715

210-196

**Item no.: 210-197**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715

210-197

**Item no.: 210-198**

Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715

210-198

**Item no.: 210-504**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715

210-504

**Item no.: 210-505**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715

210-505

**Item no.: 210-506**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715

210-506

**Item no.: 210-508**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715

210-508

**Marking accessories****Item no.: 2009-145**

Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type

2009-145

**Item no.: 2009-145/000-002**

Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type

/000-002

2009-145

**Item no.: 2009-145/000-005**

Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type

/000-005

2009-145

**Item no.: 2009-145/000-006**

Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type

/000-006

2009-145

**Item no.: 2009-145/000-007**

Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type

/000-007

2009-145

**Item no.: 2009-145/000-012**

Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type

/000-012

2009-145

**Item no.: 2009-145/000-023**

Mini-WSB Inline; for smartPRINTER; on reel; stretchable 5 - 5.2 mm; plain; snap-on type

/000-023

2009-145

**Item no.: 2009-145/000-024**

Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type

/000-024

2009-145

**Item no.: 248-501**

Miniature WSB Quick marking system; plain; Marker width 5 mm; 10 strips with 10 markers per card

248-501

**Item no.: 248-501/000-002**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type

/000-002

248-501

**Item no.: 248-501/000-005**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type

/000-005

248-501

**Item no.: 248-501/000-006**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type

/000-006

248-501

**Item no.: 248-501/000-007**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type

/000-007

248-501

**Item no.: 248-501/000-012**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type

/000-012

248-501

**Item no.: 248-501/000-017**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type

/000-017

248-501

**Item no.: 248-501/000-023**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type

/000-023

248-501

**Item no.: 248-501/000-024**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type

/000-024

248-501

**Item no.: 750-100**

Marker card; as a DIN A4 sheet; plain

750-100

**Item no.: 750-103**

Group marker carrier

750-103

**Item no.: 750-106**

Group marker carrier

750-106

**shield connection****Item no.: 790-108**

Shield clamping saddle; 11 mm wide; diameter of compatible conductor

790-108

**Item no.: 790-116**

Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm

790-116

**Item no.: 790-124**

Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm

790-124

**Item no.: 790-140**

Shield clamping saddle; diameter of compatible conductor

790-140

**Item no.: 790-208**

Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm

790-208

**Item no.: 790-216**

Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm

790-216

**Item no.: 790-220**

Shield clamping saddle; 30 mm wide; 6 ... 20 mm

790-220

**Downloads****Documentation****Manual**

|                                            |         |               |          |
|--------------------------------------------|---------|---------------|----------|
| 230V AC/DC<br>without diagnostics, passive | V 1.1.0 | pdf<br>1.9 MB | Download |
|--------------------------------------------|---------|---------------|----------|

**Bid Text**

|                       |             |                |          |
|-----------------------|-------------|----------------|----------|
| 750-612<br>IO-Klemmen | Apr 4, 2012 | doc<br>24.6 kB | Download |
|-----------------------|-------------|----------------|----------|

**Additional Information**

|                                                          |         |                 |          |
|----------------------------------------------------------|---------|-----------------|----------|
| Disposal; Electrical and electronic equipment, Packaging | V 1.0.0 | pdf<br>265.8 kB | Download |
|----------------------------------------------------------|---------|-----------------|----------|

**System Description**

|                                                                                        |         |               |          |
|----------------------------------------------------------------------------------------|---------|---------------|----------|
| Use in Hazardous Environments<br>Term definition, marking and installation regulations | V 1.0.0 | pdf<br>1.0 MB | Download |
|----------------------------------------------------------------------------------------|---------|---------------|----------|

|                                           |  |                 |          |
|-------------------------------------------|--|-----------------|----------|
| Overview on WAGO-I/O-SYSTEM 750 approvals |  | pdf<br>780.2 kB | Download |
|-------------------------------------------|--|-----------------|----------|

|                                                                                    |         |               |          |
|------------------------------------------------------------------------------------|---------|---------------|----------|
| Design Notes<br>Basic conditions and recommendations for higher operational safety | V 2.0.0 | pdf<br>1.5 MB | Download |
|------------------------------------------------------------------------------------|---------|---------------|----------|

|                                                         |  |               |          |
|---------------------------------------------------------|--|---------------|----------|
| 750/753 Series I/O-System – General Product Information |  | pdf<br>1.7 MB | Download |
|---------------------------------------------------------|--|---------------|----------|

**CAD/CAE - Smart Data****CAD data**

|                     |     |          |
|---------------------|-----|----------|
| 3D Download 750-612 | URL | Download |
|---------------------|-----|----------|

**Device Files****Device Driver**

WAGO USB Service Cable Driver / 750 and 857 Series

## Product family

### **750/753 Series I/O-System**

Learn more about the product family.

Show all products from the family



Subject to changes.