


Data sheet | Item number: 756-1404/060-020

CANopen-/DeviceNet cable, angled; 2 m; fitted on one end; A-coded; M12
plug, angled; one free cable end; violet




756-1404_060-020



RoHS Compliant

[BOMcheck.net](#)

Color:



Pin 2, 3: 0,38 mm²; Pin 4, 5: 0,67 mm²

	Schirm	
1)	rot	1
2)	schwarz	2
3)	weiss	3
4)	blau	4
5)		5

Item description

Short description:

- PUR VT, halogen-free
- Suitable for drag chains
- Good resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- Good chemical resistance
- Cable used: UL listed

Data**Technical Data**

Connection type	M12 plug - free end
No. of poles	5
Leitungsanschlussrichtung zur Steckrichtung	90°
Steckgesichtskodierung Leitung/Adapter 1 1	A coded
Cable length	2 m
Communication/Fieldbus	CANopen
Communication/Fieldbus (2)	DeviceNet
Operating voltage	≤ 300 V
Operating current	4 A
Rated surge voltage	2 kV
Contact resistance	10 MΩ
Insulation resistance	≥ 2 x 10 ⁸ Ω/km
Resistance of conductor	≤ 57 Ω/km (AWG22) + ≤ 79 Ω/km (AWG24)

Mechanical data

bending radius	min. 5 x cable Ø
Bending cycles	5 Mio.
Schleppkettentauglichkeit	yes
Cable diameter	6.6 7.2 mm
Bauartkurzzeichen	L-02YC11Y 2xAWG24 + 2xAWG22/1,4-120 VI FRNC, geschirmt
Screening	tinned copper braid, optical coverage approx. 85 %
Conductor design	Bare copper wire (19 x 0.125 mm)
Leiterisolierung	PE halogenfrei
Housing material	TPU/TPU, black (~ RAL 9005)
Tightening torque	1 Nm
Weight	151 g
Color	violet



Environmental Requirements

Umgebungstemperatur (Betrieb) bewegt	-40 +80 °C
Umgebungstemperatur (Betrieb) ruhend	-40 +80 °C
Protection class	IP67
Degree of pollution (5)	3/2 per IEC 60664-1

Commercial data

Country of origin	DE
GTIN	4045454640927
Customs Tariff No.	85444290900

Downloads

Documentation

System Description

I/O-SYSTEM – SPEEDWAY, General Product Information	pdf 1.1 MB	Download
--	---------------	--------------------------

CAD/CAE - Smart Data

WSCAD

WSCAD Universe	Download
----------------	--------------------------

Subject to changes.