


Data sheet | Item number: 756-5401/050-010

Sensor/actuator cable; fitted on both ends; 5-pole; M12 socket, straight;
M12 plug, straight; 1 m




756-5401/050-010



RoHS
Compliant

✓
BOMcheck.net



Pin 1 ... 5: 0,34 mm ²				
1	⌋	braun (+)		■ 1
2	⌋	weiß (Ö)		■ 2
3	⌋	blau (-)		■ 3
4	⌋	schwarz (S)		■ 4
5	⌋	grau		■ 5
Schirm				

Item description

Short description:

- PUR, halogen-free
- Suitable for drag chains
- Good resistance to microbes, hydrolysis, oil, chemicals and UV radiation.
- Good chemical resistance.
- Cable used: UL listed

Data

Technical Data

Connection type	M12 socket - M12 plug
No. of poles	5
Leistungsanschlussrichtung zur Steckrichtung	0°
Leistungsanschlussrichtung zur Steckrichtung (2)	0°
Steckgesichtskodierung Leitung/Adapter 1 1	A coded
Steckgesichtskodierung Leitung/Adapter 2 1	A coded
Cable length	1 m
Operating voltage	AC/DC 250 V
Operating current	4 A
Rated surge voltage	1,5 kV

Mechanical data

Bending cycles	2 Mio.
Schleppkettentauglichkeit	yes
Color of sheathed cable	black
Durchmesser der Mantelleitung	4.8 ... 5.2 mm
Sheath material	Polyurethane (OPUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Halogen-free	Yes
Housing material	Polyurethan (PUR)
Contact material	CuSn
Contact plating	CuNi/Au
Tightening torque	1 Nm
Weight	55 g

Environmental Requirements

Umgebungstemperatur (Betrieb) bewegt	-25 ... +90 °C
Umgebungstemperatur (Betrieb) ruhend	-50 ... +90 °C
Protection class	IP67
Degree of pollution (5)	3 acc. to VDE 0110

Commercial data

Country of origin	HU
GTIN	4044918975605
Customs Tariff No.	85444290900



Downloads
Documentation
System Description

IP67 Cables and Pluggable Connectors

pdf
293.9 kB

Download



Subject to changes.