



757-284/000-025



Item description

- M12 sensor/actuator box, 8-way
- 4-pole (1 signal per contact)
- Cable length 5m, 10m and 25 m

- Green LED operating indicator
- Yellow LED status indicator
- incl. tag labels (10 pcs)
- incl. M12 protective caps (2 pcs)

Data

Technical Data

Contact resistance max.	0.01 Ω
Supply voltage	DC 10 ... 30 V; Bemessungsspannung: 32 V ~ eff.
Current carrying capacity of the signal connections	2 A
Current carrying capacity of the supply connections	9 A
Bemessungswert der galvanischen Trennung	500 V
Funktional getrennte Potentialgruppen	Kontakt/Kontakt
Insulation resistance	1000 M Ω
Signal characteristic	PNP
Indicators	LED (A) yellow: Signal status (1 x per contact); LED (U) green: Sensor /actuator box status

Connection data

Connection technology: In-/Outputs	8 x M12 connectors, 4 poles, incl. PE
Connection technology: trunk cable	1 x feste Anschlussleitung
Length of the connecting cable	25 m
Strip length	100 mm / 3.94 inch
Colors of the leads	white, green, yellow, gray, pink, red, black, purple, green/yellow, brown, blue
Conductor cross section	Cross section of single conductor: 0.34 mm ² ; Cross section of single conductor (2): 1 mm ²

Geometrical Data

Width	60 mm / 2.362 inch
Height	26 mm / 1.024 inch
Depth	152 mm / 5.984 inch

Mechanical data

Mounting type	Screw mounting
---------------	----------------

Material Data

Housing material	PA 66 (UL 94 V0); RAL 7035; silicon and halogen free
Halogen-free	Yes
Durchmesser der Mantelleitung	8.2 mm

bending radius	min. 10 x cable Ø
Materialeigenschaften der Anschlüsse	Contact: CuSn, pre-nickel- and 0.8 µm gold-plated; Tapped bush: Zn diecast nickel-plated; Seal: Viton; Connection cycles: 50
Sheath material	PUR
Color of sheathed cable	black
Potting	Fully encapsulated with conformal coating (UL 94 V0)

Environmental Requirements

Surrounding air (operating) temperature	-25 ... 80 °C
Umgebungstemperatur (Betrieb) bewegt	-5 ... +80 °C
Umgebungstemperatur (Betrieb) ruhend	-40 ... +80 °C
Protection class	IP68
Degree of pollution (5)	3 acc. to VDE 0110
Vibration resistance	acc. to IEC 60068-2-6
Shock resistance	acc. to IEC 60068-2-27

Commercial data

Country of origin	DE
GTIN	4045454478964
Customs Tariff No.	85366990990

Compatible products

Marking accessories

	Item no.: 210-110 Fiber-tip pen	210-110
	Item no.: 757-011 Marker card; not stretchable; snap-on type	757-011

General accessories

	Item no.: 756-8102 M12 protective cap; for unused sockets	756-8102
	Item no.: 757-080 Spacer module for sensor/actuator box; 8-way	757-080

Downloads

Documentation

Additional Information

Disposal; Electrical and electronic equipment, Packaging	V 1.0.0	pdf 265.8 kB	Download
--	---------	-----------------	----------




System Description

Sensor/Actuator Boxes – General Product Information	pdf 537.3 kB	Download
---	-----------------	----------

CAD/CAE - Smart Data

CAD data

3D Download 757-284/000-025	URL	Download
-----------------------------	-----	----------



Subject to changes.