


Data sheet | Item number: 769-609/001-000

1-conductor male connector; Snap-in mounting feet; 4 mm²; Pin spacing 5 mm; 9-pole; 4,00 mm2; gray



769-609_001-000



RoHS
Compliant

BOMcheck.net

Color: ■

Data

Electrical data

Ratings per IEC/EN 60664-1

Rated voltage (III / 3)	500 V
Rated impulse voltage (III / 3)	6 kV
Rated current	32 A

Connection data

Connection technology	CAGE CLAMP®
Actuation type	Operating tool
Connectable conductor materials	Copper
Nominal cross section	4 mm²
Solid conductor	0.08 4 mm² / 28 12 AWG
Fine-stranded conductor	0.08 4 mm² / 28 12 AWG
Strip length	8 9 mm / 0.31 0.35 inch
Total number of connection points	9

Total number of potentials	9
Type of wiring	Front-entry wiring
No. of poles	9

Geometrical Data

Pin spacing	5 mm / 0.197 inch
Width	48.6 mm / 1.913 inch
Height from the surface	18.3 mm / 0.72 inch
Depth	40.2 mm / 1.583 inch

Mechanical data

Mounting type	Snap-in mounting foot
---------------	-----------------------

Plug connection

Contact type (pluggable connector)	Male connector/plug
Connector connection type	for conductors

Material Data

Color	gray
Insulating material	Polyamide 66 (PA 66)
Fire load	0.523 MJ
Weight	26.458 g

Commercial data

Product Group	18 (X-COM-System)
Country of origin	PL
GTIN	4044918522113
Customs Tariff No.	85366990990

Approvals / Certificates

Radio-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	CCA	EN 61984	2190419.02
	CCA	IEC 61984	NL-47799
	CCA DEKRA Certification B.V.	EN 60947	NTR NL-7626

CCA



CSA
DEKRA Certification B.V.

C22.2 No. 158

1101144



KEMA/KEUR
DEKRA Certification B.V.

EN 60947

2190419.01

Country specific Approvals

Logo	Approval	Additional Approval Text	Certificate name
	CCA DEKRA Certification B.V.	IEC 61984	NL-47799
CCA	CCA DEKRA Certification B.V.	EN 60947	NTR NL-7626
KEMA/KEUR	CCA DEKRA Certification B.V.	EN 61984	2190419.02
CSA	CSA DEKRA Certification B.V.	C22.2 No. 158	1101144
KEMA/KEUR	KEMA/KEUR DEKRA Certification B.V.	EN 60947	2190419.01

Other Approvals

Logo	Approval	Additional Approval Text	Certificate name
UL	UL Underwriters Laboratories Inc.	UL 1977	E45171
UL	UL Underwriters Laboratories Inc.	UL 1059	E45172

UL-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	UR Underwriters Laboratories Inc.	UL 1059	31.07.2019- E45172
	UR Underwriters Laboratories Inc.	UL 1977	E45171- 20010720

Compatible products

Strain relief plate

	Item no.: 769-410 Strain relief plate; gray	769-410
	Item no.: 769-413 Strain relief plate; gray	769-413

ferrule

	Item no.: 216-101 Ferrule; Sleeve for 0.5 mm ² / AWG 22; uninsulated; electro-tin plated	216-101
	Item no.: 216-102 Ferrule; Sleeve for 0.75 mm ² / AWG 20; uninsulated; electro-tin plated	216-102
	Item no.: 216-103 Ferrule; Sleeve for 1 mm ² / AWG 18; uninsulated; electro-tin plated	216-103
	Item no.: 216-104 Ferrule; Sleeve for 1.5 mm ² / AWG 16; uninsulated; electro-tin plated	216-104
	Item no.: 216-201 Ferrule; Sleeve for 0.5 mm ² / 20 AWG; insulated; electro-tin plated; white	216-201
	Item no.: 216-202 Ferrule; Sleeve for 0.75 mm ² / 18 AWG; insulated; electro-tin plated; gray	216-202
	Item no.: 216-203 Ferrule; Sleeve for 1 mm ² / AWG 18; insulated; electro-tin plated; red	216-203
	Item no.: 216-204 Ferrule; Sleeve for 1.5 mm ² / AWG 16; insulated; electro-tin plated; black	216-204

**Item no.: 216-206**Ferrule; Sleeve for 2.5 mm² / AWG 14; insulated; electro-tin plated; blue

216-206

Marking accessories

	Item no.: 2009-145 Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type; white		2009-145
	Item no.: 2009-145/000-002 Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type; yellow	/000-002	2009-145
	Item no.: 2009-145/000-005 Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type; red	/000-005	2009-145
	Item no.: 2009-145/000-006 Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type; blue	/000-006	2009-145
	Item no.: 2009-145/000-007 Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type; gray	/000-007	2009-145
	Item no.: 2009-145/000-012 Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type; orange	/000-012	2009-145
	Item no.: 2009-145/000-023 Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type; green	/000-023	2009-145
	Item no.: 2009-145/000-024 Mini-WSB Inline; for Smart Printer; on reel; stretchable 5 - 5.2 mm; plain; snap-on type; violet	/000-024	2009-145
	Item no.: 210-831 Marking strips; on reel; 2.3 mm wide; plain; Self-adhesive; white		210-831
	Item no.: 210-832 Marking strips; on reel; 3 mm wide; plain; Self-adhesive; white		210-832
	Item no.: 210-833 Marking strips; on reel; 6 mm wide; plain; Self-adhesive; white		210-833
	Item no.: 210-834 Marking strips; on reel; 5 mm wide; plain; Self-adhesive; white		210-834
	Item no.: 248-501 Miniature WSB Quick marking system; plain; Marker width 5 mm; 10 strips with 10 markers per card		248-501
	Item no.: 248-501/000-002 Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow	/000-002	248-501
	Item no.: 248-501/000-005 Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white	/000-005	248-501

**Item no.: 248-501/000-006**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

/000-006

248-501

**Item no.: 248-501/000-007**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

/000-007

248-501

**Item no.: 248-501/000-012**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

/000-012

248-501

**Item no.: 248-501/000-017**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

/000-017

248-501

**Item no.: 248-501/000-023**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

/000-023

248-501

**Item no.: 248-501/000-024**

Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

/000-024

248-501

tools**Item no.: 210-490**

Operating tool; for female and male connectors with CAGE CLAMP® connection

210-490

**Item no.: 769-434**

Push-button; loose

769-434

Coding**Item no.: 769-435**

Coding pin; for coding of female plugs; for carrier terminal blocks / male connectors; orange

769-435

Female plug**Item no.: 769-101**1-conductor female plug; 4 mm²; 1-pole; 4,00 mm²; gray

769-101

**Item no.: 769-101/000-016**1-conductor female plug; 4 mm²; 1-pole; 4,00 mm²; green-yellow

/000-016

769-101

**Item no.: 769-102**1-conductor female plug; 4 mm²; 2-pole; 4,00 mm²; gray

769-102

**Item no.: 769-102/000-036**1-conductor female plug; 4 mm²; 2-pole; 4,00 mm²; gray, green-yellow

/000-036

769-102

**Item no.: 769-102/000-037**1-conductor female plug; 4 mm²; 2-pole; 4,00 mm²; green-yellow, gray

/000-037

769-102

**Item no.: 769-103**1-conductor female plug; 4 mm²; 3-pole; 4,00 mm²; gray

769-103

	Item no.: 769-103/000-036 1-conductor female plug; 4 mm ² ; 3-pole; 4,00 mm ² ; gray, green-yellow	/000-036	769-103
	Item no.: 769-103/000-037 1-conductor female plug; 4 mm ² ; 3-pole; 4,00 mm ² ; green-yellow, gray	/000-037	769-103
	Item no.: 769-103/000-038 1-conductor female plug; 4 mm ² ; 3-pole; 4,00 mm ² ; gray, blue, green-yellow	/000-038	769-103
	Item no.: 769-103/000-039 1-conductor female plug; 4 mm ² ; 3-pole; 4,00 mm ² ; green-yellow, blue, gray	/000-039	769-103
	Item no.: 769-104 1-conductor female plug; 4 mm ² ; 4-pole; 4,00 mm ² ; gray		769-104
	Item no.: 769-104/000-036 1-conductor female plug; 4 mm ² ; 4-pole; 4,00 mm ² ; gray, green-yellow	/000-036	769-104
	Item no.: 769-104/000-037 1-conductor female plug; 4 mm ² ; 4-pole; 4,00 mm ² ; green-yellow, gray	/000-037	769-104
	Item no.: 769-104/000-038 1-conductor female plug; 4 mm ² ; 4-pole; 4,00 mm ² ; gray, blue, green-yellow	/000-038	769-104
	Item no.: 769-104/000-039 1-conductor female plug; 4 mm ² ; 4-pole; 4,00 mm ² ; green-yellow, blue, gray	/000-039	769-104
	Item no.: 769-105 1-conductor female plug; 4 mm ² ; 5-pole; 4,00 mm ² ; gray		769-105
	Item no.: 769-105/000-036 1-conductor female plug; 4 mm ² ; 5-pole; 4,00 mm ² ; gray, green-yellow	/000-036	769-105
	Item no.: 769-105/000-037 1-conductor female plug; 4 mm ² ; 5-pole; 4,00 mm ² ; green-yellow, gray	/000-037	769-105
	Item no.: 769-105/000-038 1-conductor female plug; 4 mm ² ; 5-pole; 4,00 mm ² ; gray, blue, green-yellow	/000-038	769-105
	Item no.: 769-105/000-039 1-conductor female plug; 4 mm ² ; 5-pole; 4,00 mm ² ; green-yellow, blue, gray	/000-039	769-105
	Item no.: 769-106 1-conductor female plug; 4 mm ² ; 6-pole; 4,00 mm ² ; gray		769-106

**Item no.: 769-106/000-006**1-conductor female plug; 4 mm²; 6-pole; 4,00 mm²; blue

769-106

/000-006

**Item no.: 769-106/000-036**1-conductor female plug; 4 mm²; 6-pole; 4,00 mm²; gray, green-yellow

769-106

/000-036

**Item no.: 769-106/000-037**1-conductor female plug; 4 mm²; 6-pole; 4,00 mm²; green-yellow, gray

769-106

/000-037

**Item no.: 769-106/000-038**1-conductor female plug; 4 mm²; 6-pole; 4,00 mm²; gray, blue, green-yellow

769-106

/000-038

**Item no.: 769-106/000-039**1-conductor female plug; 4 mm²; 6-pole; 4,00 mm²; green-yellow, blue, gray

769-106

/000-039

**Item no.: 769-107**1-conductor female plug; 4 mm²; 7-pole; 4,00 mm²; gray

769-107

**Item no.: 769-107/000-036**1-conductor female plug; 4 mm²; 7-pole; 4,00 mm²; gray, green-yellow

769-107

/000-036

**Item no.: 769-107/000-037**1-conductor female plug; 4 mm²; 7-pole; 4,00 mm²; green-yellow, gray

769-107

/000-037

**Item no.: 769-107/000-038**1-conductor female plug; 4 mm²; 7-pole; 4,00 mm²; gray, blue, green-yellow

769-107

/000-038

**Item no.: 769-107/000-039**1-conductor female plug; 4 mm²; 7-pole; 4,00 mm²; green-yellow, blue, gray

769-107

/000-039

**Item no.: 769-108**1-conductor female plug; 4 mm²; 8-pole; 4,00 mm²; gray

769-108

**Item no.: 769-108/000-036**1-conductor female plug; 4 mm²; 8-pole; 4,00 mm²; gray, green-yellow

769-108

/000-036

**Item no.: 769-108/000-037**1-conductor female plug; 4 mm²; 8-pole; 4,00 mm²; green-yellow, gray

769-108

/000-037

**Item no.: 769-108/000-038**1-conductor female plug; 4 mm²; 8-pole; 4,00 mm²; gray, blue, green-yellow

769-108

/000-038

**Item no.: 769-108/000-039**1-conductor female plug; 4 mm²; 8-pole; 4,00 mm²; green-yellow, blue, gray

769-108

/000-039

**Item no.: 769-109**1-conductor female plug; 4 mm²; 9-pole; 4,00 mm²; gray

769-109

**Item no.: 769-109/000-036**1-conductor female plug; 4 mm²; 9-pole; 4,00 mm²; gray, green-yellow

/000-036

769-109

**Item no.: 769-109/000-037**1-conductor female plug; 4 mm²; 9-pole; 4,00 mm²; green-yellow, gray

/000-037

769-109

**Item no.: 769-109/000-038**1-conductor female plug; 4 mm²; 9-pole; 4,00 mm²; gray, blue, green-yellow

/000-038

769-109

**Item no.: 769-109/000-039**1-conductor female plug; 4 mm²; 9-pole; 4,00 mm²; green-yellow, blue, gray

/000-039

769-109

**Item no.: 769-109/021-000**1-conductor female plug; Locking lever; 4 mm²; 9-pole; 4,00 mm²; gray

/021-000

769-109

**Item no.: 769-121**2-conductor female connector; 4 mm²; 1-pole; 4,00 mm²; gray

769-121

**Item no.: 769-122**2-conductor female connector; 4 mm²; 2-pole; 4,00 mm²; gray

769-122

**Item no.: 769-123**2-conductor female connector; 4 mm²; 3-pole; 4,00 mm²; gray

769-123

**Item no.: 769-124**2-conductor female connector; 4 mm²; 4-pole; 4,00 mm²; gray

769-124

**Item no.: 769-125**2-conductor female connector; 4 mm²; 5-pole; 4,00 mm²; gray

769-125

**Item no.: 769-126**2-conductor female connector; 4 mm²; 6-pole; 4,00 mm²; gray

769-126

**Item no.: 769-127**2-conductor female connector; 4 mm²; 7-pole; 4,00 mm²; gray

769-127

**Item no.: 769-128**2-conductor female connector; 4 mm²; 8-pole; 4,00 mm²; gray

769-128

**Item no.: 769-129**2-conductor female connector; 4 mm²; 9-pole; 4,00 mm²; gray

769-129

Insulation stop**Item no.: 769-470**Insulation stop; 0.08 - 0.2 mm² "s" (0.14 mm² "f-st"); 5 pieces/strip; white

769-470

**Item no.: 769-471**Insulation stop; 0.25 - 0.5 mm²; 5 pieces/strip; light gray

769-471

**Item no.: 769-472**Insulation stop; 0.75 - 1 mm²; 5 pieces/strip; dark gray

769-472

Protective Warning Marker



Item no.: 280-415

Protective warning marker; with high-voltage symbol, black; for 5 terminal blocks; yellow

280-415

assembling



Item no.: 209-137

Mounting adapter; can be used as end plate; 6.5 mm wide; gray

209-137

Downloads

Documentation

Bid Text

769-609/001-000

doc
25.6 kB

Download

Additional Information

Technical explanations

Apr 3, 2019

pdf
2.1 MB

Download

CAD/CAE - Smart Data

CAD data

3D Download 769-609/001-000

URL

Download

EPLAN

EPLAN Data Portal

Download

WSCAD

WSCAD Universe

Download

Product family

X-COM

Show all products from the family

Subject to changes.