


Data sheet | Item number: 884-3000

Stud terminal block; 300 mm²; with 2 stud bolts M16; 300,00 mm²; beige

www.wago.com/884-3000



Color: 



Data

Electrical data

IEC Approvals

Rated voltage (III / 3)	1000 V
Rated surge voltage (III/3)	8 kV
Rated current	520 A
Legend (ratings)	(III / 3) ≙ Overvoltage category III / Pollution degree 3

UL Approvals

Approvals per	UL 1059
Rated voltage UL (Use Group B)	1000 V
Rated current UL (Use Group B)	420 A
Rated current UL (Use Group B), factory wiring only	510 A
Rated voltage UL (Use Group C)	1000 V
Rated current UL (Use Group C)	420 A
Rated current UL (Use Group C), factory wiring only	510 A

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.



CSA Approvals

Approvals per	C22.2 No 158
Rated voltage CSA (Use Group B)	1000 V
Rated current CSA (Use Group B)	510 A
Rated voltage CSA (Use Group C)	1000 V
Rated current CSA (Use Group C)	510 A

Connection data

Connection technology	Bolt-type connection
Actuation type	Open-end, ring, socket wrench
Connectable conductor materials	Copper
Nominal cross-section	300 mm ²
Total number of connection points	2
Total number of potentials	1
Number of levels	1
Connection position	top
Clamping range	25 ... 300 mm ² / 6 AWG ... 600 kcmil
Type of cable lugs according to DIN 46234	Cable lugs for solder-free connections Ring type, without insulating sleeve, for copper conductors
DIN46234: 1 cable lug per side	25 ... 240 mm ²
DIN 46234: 2 cable lugs per side	50 ... 240 mm ²
Type of cable lugs according to DIN 46235	Cable lugs for compression connections Cover plate type for copper conductors
DIN46235: 1 cable lug per side	50 ... 300 mm ²
DIN 46235: 2 cable lugs per side	50 ... 240 mm ²
Bolt thread	M16

Physical data

Width	55 mm / 2.165 inch
Height	164 mm / 6.457 inch
Depth from upper edge of DIN-rail	86 mm / 3.386 inch

Mechanical data

Tightening torque	25 ... 60 Nm
Mounting type	DIN-35 rail Panel mounting

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.



Material data

Color	beige
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Weight	510 g

Environmental requirements

Continuous operating temperature	-40 ... +120 °C
----------------------------------	-----------------

Commercial data

Packaging type	BOX
Country of origin	DE
GTIN	4055143941952
Customs tariff number	8536904000

Optional accessories

Marking accessories

*	Item no.: 2009-115 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white	www.wago.com/2009-115
*	Item no.: 2009-115/000-002 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow	www.wago.com/2009-115/000-002
*	Item no.: 2009-115/000-005 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red	www.wago.com/2009-115/000-005
*	Item no.: 2009-115/000-006 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue	www.wago.com/2009-115/000-006
*	Item no.: 2009-115/000-007 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray	www.wago.com/2009-115/000-007
*	Item no.: 2009-115/000-012 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange	www.wago.com/2009-115/000-012
*	Item no.: 2009-115/000-017 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; light green	www.wago.com/2009-115/000-017

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.



	Item no.: 2009-115/000-023 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green	www.wago.com/2009-115/000-023
	Item no.: 2009-115/000-024 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet	www.wago.com/2009-115/000-024
	Item no.: 793-501 WMB marking card; as card; not stretchable; plain; snap-on type; white	www.wago.com/793-501
	Item no.: 793-501/000-002 WMB marking card; as card; not stretchable; plain; snap-on type; yellow	www.wago.com/793-501/000-002
	Item no.: 793-501/000-005 WMB marking card; as card; not stretchable; plain; snap-on type; red	www.wago.com/793-501/000-005
	Item no.: 793-501/000-006 WMB marking card; as card; not stretchable; plain; snap-on type; blue	www.wago.com/793-501/000-006
	Item no.: 793-501/000-007 WMB marking card; as card; not stretchable; plain; snap-on type; gray	www.wago.com/793-501/000-007
	Item no.: 793-501/000-012 WMB marking card; as card; not stretchable; plain; snap-on type; orange	www.wago.com/793-501/000-012
	Item no.: 793-501/000-017 WMB marking card; as card; not stretchable; plain; snap-on type; light green	www.wago.com/793-501/000-017
	Item no.: 793-501/000-023 WMB marking card; as card; not stretchable; plain; snap-on type; green	www.wago.com/793-501/000-023
	Item no.: 793-501/000-024 WMB marking card; as card; not stretchable; plain; snap-on type; violet	www.wago.com/793-501/000-024
	Item no.: 793-5501 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white	www.wago.com/793-5501
	Item no.: 793-5501/000-002 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; yellow	www.wago.com/793-5501/000-002
	Item no.: 793-5501/000-005 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; red	www.wago.com/793-5501/000-005

Subject to changes. Please also observe the further product documentation!



	Item no.: 793-5501/000-006 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; blue	www.wago.com/793-5501/000-006
	Item no.: 793-5501/000-007 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; gray	www.wago.com/793-5501/000-007
	Item no.: 793-5501/000-012 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; orange	www.wago.com/793-5501/000-012
	Item no.: 793-5501/000-014 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; brown	www.wago.com/793-5501/000-014
	Item no.: 793-5501/000-017 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; green	www.wago.com/793-5501/000-017
	Item no.: 793-5501/000-023 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; light green	www.wago.com/793-5501/000-023
	Item no.: 793-5501/000-024 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; violet	www.wago.com/793-5501/000-024
Mounting		
	Item no.: 249-117 Screwless end stop; 10 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray	www.wago.com/249-117
	Item no.: 249-197 Screwless end stop; 14 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray	www.wago.com/249-197
	Item no.: 884-3080 Cover; for stud terminal block; 185 and 300 mm ² ; beige	www.wago.com/884-3080
	Item no.: 884-3084 Cover; for stud terminal block; 185 and 300 mm ² ; blue	www.wago.com/884-3084
	Item no.: 884-3086 Cover; for stud terminal block; 185 and 300 mm ² ; yellow	www.wago.com/884-3086
Carrier rail		
	Item no.: 210-112 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm; silver-colored	www.wago.com/210-112
	Item no.: 210-113 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored	www.wago.com/210-113
	Item no.: 210-114	www.wago.com/210-114

Subject to changes. Please also observe the further product documentation!



	Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored		
	Item no.: 210-115 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm; www.wago.com/210-115 silver-colored		
	Item no.: 210-118 Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored		www.wago.com/210-118
	Item no.: 210-197 Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715; silver-colored		www.wago.com/210-197
	Item no.: 210-198 Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored		www.wago.com/210-198
	Item no.: 210-504 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715; silver-colored		www.wago.com/210-504
	Item no.: 210-505 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715; silver-colored		www.wago.com/210-505
	Item no.: 210-506 Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715; silver-colored		www.wago.com/210-506
	Item no.: 210-508 Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715; silver-colored		www.wago.com/210-508
Jumpers			
	Item no.: 884-3042 Jumper; for M16 stud bolts; 2-way; unplated; white		www.wago.com/884-3042
	Item no.: 884-3043 Jumper; for M16 stud bolts; 3-way; unplated; silver-colored		www.wago.com/884-3043

Downloads

Documentation

Additional Information

Technical explanations	Apr 3, 2019	pdf 2.2 MB	Download
------------------------	-------------	---------------	----------

CAD files

CAD data

2D/3D Models 884-3000	URL	Download
-----------------------	-----	----------

CAE data

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.

Environmental Product Compliance

Compliance Search


Environmental Product Compliance 884-3000

[URL](#)

[Download](#)

Stud terminal block; 300 mm²; with 2 stud bolts M16; 300,00 mm²; beige

Installation Notes



Conductor termination

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us


Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.



Anschluss von zwei Kabelschuhen an einen Gewindebolzen

Es ist möglich, bis zu zwei Kabelschuhe an einem Gewindebolzen anzuschließen. Dafür werden die Kabelschuhe mit den Rückseiten zueinander auf den Bolzen gesetzt. Anschließend wird die Sechskant-Kombimutter mit dem erforderlichen Drehmoment angezogen, sodass sich die Laschen der Kabelschuhe gegeneinanderpressen und sicher mit der Stromschiene kontaktiert werden.

Commoning




Brücken

Schritt 1: Die inneren Trennwände neben den Gewindebolzen entfernen.
Schritt 2: Den 2- oder 3-fach-Brücker auf die zu verbindenden Gewindebolzen auflegen.
Schritt 3: Die Sechskant-Kombimuttern mit dem erforderlichen Drehmoment anziehen.
Achtung: Die Brücker werden unter dem anzuschließenden Ringkabelschuh positioniert.
Die Brücker sind für den Bemessungsstrom der jeweiligen Bolzenklemme ausgelegt.

Subject to changes. Please also observe the further product documentation!

Cover



Abdeckprofil:

Die Abdeckprofile werden in die vorgesehenen Rastelemente der Bolzenklemme von oben aufgerastet. Es besteht die Möglichkeit, die Abdeckprofile mit einem Schneidwerkzeug zu kürzen. Die Abdeckprofile lassen sich ein- oder beidseitig montieren und gewährleisten einen zuverlässigen Berührungsschutz.

Testing



Prüfen


Spannungsmessungen lassen sich direkt an den Gewindebolzen durchführen. Durch die vorgesehenen Prüföffnungen werden Spannungsmessungen auch mit montierten Warnabdeckungen ermöglicht.

Marking

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.



Beschriftung

Die Bolzenklemmen lassen sich schnell und einfach mit dem Beschriftungssystem WMB Inline beschriften. Die Schilder werden in die dafür vorgesehenen Aufnahmen eingesetzt. Beschriftungsstreifen werden mithilfe der Beschriftungsadapter (2009-198) eingesetzt.

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at (262) 255-6222 or 1 800-DIN-RAIL.