
JENN-AIR® DETAILED PLANNING DIMENSIONS


UNDER COUNTER WINE CELLARS

JUW24FRERS, JUW24FLERS – 23⅞" x 34⅜" x 26" (including handle)
JUW24FRECX, JUW24FLECX – 23⅞" x 34⅜" x 23⅞"

PRODUCT DIMENSIONS



FRONT VIEW



TOP VIEW

MODEL #		JUW24FRERS JUW24FLERS JUW24FRECX JUW24FLECX	
		in	cm
A	Width of door	23¾	60.3
B	Width of grille	23¾	60.2
C	Height to top of handle Pro-Style® Stainless*	28¼	71.7
	Euro-Style Stainless	28	71.1
	Custom panel	**	**
D	Height of door	30⅛	76.6
E†	Height with hinge cover (min.)	34⅜	87.4
F	Height of grille	3¾	9.4
G	Width with hinge cover	23⅞	60.6
H	Width from side of wine cellar to handle – door open 90° Pro-Style® Stainless*	2⅝	6.7
	Euro-Style Stainless	2⅛	5.3
	Custom panel	**	**
I	Depth without door	21⅝	55.0
J‡	Depth with door	23⅞	60.7
K	Depth with handle Pro-Style® Stainless*	26½	67.4
	Euro-Style Stainless	26	66.0
	Custom panel	**	**
L	Depth with door open 90°	47¾	121.4

*Requires optional Pro-Style® Stainless handle kit – W10588599. Each kit includes one Pro-Style® badge and one handle.
**For custom panel models, this depends on handle chosen.
†Add ⅝" (1.6 cm) to the height dimension when leveling legs are fully extended.
‡Includes recommended ¾" (1.9 cm) custom panel thickness (JUW24FRECX, JUW24FLECX).

IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation or Use & Care Guide *before* selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.


JENN-AIR®

JENN-AIR® DETAILED PLANNING DIMENSIONS

UNDER COUNTER WINE CELLARS

JUW24FRERS, JUW24FLERS – 23⅞" x 34⅜" x 26" (including handle)
JUW24FRECX, JUW24FLECX – 23⅞" x 34⅜" x 23⅞"

DIMENSIONS AS INSTALLED



SIDE VIEW

MODEL #		JUW24FRERS JUW24FLERS JUW24FRECX JUW24FLECX	
		in	cm
A*	Height with hinge cover (min.)	34⅜	87.4
B*	Height to top of door (min.)	34⅛	86.8
C*	Height to top of handle (min.) Pro-Style® Stainless**	28¼	71.7
	Euro-Style Stainless	28	71.1
	Custom panel	†	†
D*	Height to top of grille (min.)	4	10.2
E*	Height of recessed wine cellar (min.)	34⅛	86.8
F	Depth with door open 90° (min.)	47¾	121.4
G	Depth with handle (min.) Pro-Style® Stainless**	26½	67.4
	Euro-Style Stainless	26	66.0
	Custom panel	†	†
H‡	Depth with door (min.)	24	60.9
I	Depth without door (min.)	21⅝	55.0
J	Depth of grille (min.)	20¾	52.7

*Add ⅝" (1.6 cm) to the height dimension when leveling legs are fully extended.

**Requires optional Pro-Style® Stainless handle kit – W10588599. Each kit includes one Pro-Style® badge and one handle.

†For custom panel models, this depends on handle chosen.

‡Includes recommended ¾" (1.9 cm) custom panel thickness (JUW24FRECX, JUW24FLECX).

IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation or Use & Care Guide *before* selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.


JENN-AIR®

JENN-AIR® DETAILED PLANNING DIMENSIONS


UNDER COUNTER WINE CELLARS

JUW24FRERS, JUW24FLERS – 23⅞" x 34⅜" x 26" (including handle)
JUW24FRECX, JUW24FLECX – 23⅞" x 34⅜" x 23⅞"


OPENING/CLEARANCE DIMENSIONS



FRONT VIEW



SIDE VIEW



BACK VIEW

MODEL #		JUW24FRERS JUW24FLERS JUW24FRECX JUW24FLECX	
		in	cm
A	Width (min.)	24	61.0
B	Minimum width from hinged side of wine cellar to fixed wall – door open 90°	1⅝	4.0
C	Height (min.)	34⅜	87.3
D	Depth (min.)	24	61.0

VENTILATION REQUIREMENTS

For proper ventilation, allow ¼" (0.6 cm) space on the top and each side.

ELECTRICAL REQUIREMENTS

115 volt, 60 Hz, AC only, 15- or 20-amp fused, grounded circuit is required. A dedicated circuit is recommended. Use an outlet that cannot be turned off by a switch. Minimum length of the power cord is 63" (160.0 cm). Do not use an extension cord.

IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation or Use & Care Guide *before* selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.

JENN-AIR®